

MC79L05ACLPME3

MC79L05ACLPME3 Information

War V. Heisenen.com	 MC79L05ACLPME3 Texas Instruments Integrated Circuits (ICs) PMIC - Voltage Regulators - Linear IC REG LINEAR -5V 100MA TO92-3 TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MC79L05ACLPME3 Specifications

Manufacturer Texas Instruments Manufacturer Integrated Circuits (ICs) PMIC - Voltage Regulators - Linear Package TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Series - Output Configuration Negative Number of Regulators 1 Voltage - Input (Max) -20V Voltage - Output (Max) -20V Voltage - Output (Max) -5V Voltage - Output (Max) - Voltage Dropout (Max) - Current - Output 100mA Current - Quiescent (Iq) - Current - Supply (Max) - PSRR 49dB (120Hz) Control Features Over Temperature, Short Circuit Operating Temperature 0ver Temperature, Short Circuit Operating Temperature 0°C ~ 125°C Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226A) (Formed Leads) Supplier Device Package TO-92-3		
CategoryIntegrated Circuits (ICs)PMIC - Voltage Regulators - LinearPackageTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Package-Output ConfigurationNegativeOutput ConfigurationNegativeOutput TypeFixedNumber of Regulators1Voltage - Input (Max)-20VVoltage - Output (Min/Fixed)-5VVoltage - Output (Max)-Voltage Dropout (Max)1.7V @ 40mACurrent - Output100mACurrent - Quiescent (Iq)-Current - Supply (Max)-PSRR49dB (120Hz)Control FeaturesOver Temperature, Short CircuitOperating Temperature0°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Manufacturer Part Number	MC79L05ACLPME3
PMIC - Voltage Regulators - LinearPackageTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Series-Output ConfigurationNegativeDutput TypeFixedNumber of Regulators1Voltage - Input (Max)-20VVoltage - Output (Min/Fixed)-5VVoltage - Output (Max)-Voltage Dropout (Max)-Current - Output100mACurrent - Quiescent (Iq)-Current - Supply (Max)-PSRR49dB (120Hz)Portection Features-Protection Features-Over Temperature, Short Circuit0°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3Supplier Device PackageTO-92-3	Manufacturer	Texas Instruments
PackageTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Series-Output ConfigurationNegativeOutput TypeFixedNumber of Regulators1Voltage - Input (Max)-20VVoltage - Output (Min/Fixed)-5VVoltage - Output (Max)-Voltage - Output (Max)-Voltage Dropout (Max)-Current - Output100mACurrent - Quiescent (Iq)-Current - Supply (Max)-PSRR49dB (120Hz)Potection Features-Protection FeaturesOver Temperature, Short CircuitOperating TemperatureOfer 2125°CMounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Category	Integrated Circuits (ICs)
Series-Output ConfigurationNegativeOutput TypeFixedNumber of Regulators1Voltage - Input (Max)-20VVoltage - Output (Min/Fixed)-5VVoltage - Output (Max)-Voltage - Output (Max)1.7V @ 40mACurrent - Output100mACurrent - Quiescent (Iq)-Current - Supply (Max)-PSRR49dB (120Hz)Control Features-Protection Features0ver Temperature, Short CircuitOperating Temperature0°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-922-3 (TO-926AA) (Formed Leads)Supplier Device PackageTO-92-3		PMIC - Voltage Regulators - Linear
Output Configuration Negative Output Type Fixed Number of Regulators 1 Voltage - Input (Max) -20V Voltage - Output (Min/Fixed) -5V Voltage - Output (Max) - Voltage - Output (Max) - Voltage - Output (Max) - Voltage Dropout (Max) 1.7V @ 40mA Current - Output 100mA Current - Quiescent (Iq) - Current - Supply (Max) - PSRR 49dB (120Hz) Control Features - Protection Features Over Temperature, Short Circuit Operating Temperature 0°C ~ 125°C Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package To-92-3	Package	TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)
Output TypeFixedNumber of Regulators1Voltage - Input (Max)-20VVoltage - Output (Min/Fixed)-5VVoltage - Output (Max)-Voltage Dropout (Max)1.7V @ 40mACurrent - Output100mACurrent - Quiescent (Iq)-Current - Supply (Max)-PSRR49dB (120Hz)Control FeaturesOver Temperature, Short CircuitOperating Temperature0°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-92-3 (TO-926A) (Formed Leads)Supplier Device PackageTO-92-3	Series	-
Number of Regulators1Number of Regulators-20VVoltage - Input (Max)-5VVoltage - Output (Min/Fixed)-5VVoltage - Output (Max)-Voltage Dropout (Max)1.7V @ 40mACurrent - Output100mACurrent - Quiescent (Iq)-Current - Supply (Max)-PSRR49dB (120Hz)Control Features-Protection FeaturesOver Temperature, Short CircuitOperating Temperature0°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Output Configuration	Negative
Voltage - Input (Max) -20V Voltage - Output (Min/Fixed) -5V Voltage - Output (Max) - Voltage Dropout (Max) 1.7V @ 40mA Current - Output 100mA Current - Quiescent (Iq) - Current - Supply (Max) - PSRR 49dB (120Hz) Control Features - Protection Features Over Temperature, Short Circuit Operating Temperature 0°C ~ 125°C Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)	Output Type	Fixed
Voltage - Output (Min/Fixed)-5VVoltage - Output (Max)-Voltage Dropout (Max)1.7V @ 40mACurrent - Output100mACurrent - Quiescent (Iq)-Current - Supply (Max)-PSRR49dB (120Hz)Control Features-Protection FeaturesOver Temperature, Short CircuitOperating Temperature0°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Number of Regulators	1
Voltage - Output (Max)-Voltage Dropout (Max)1.7V @ 40mACurrent - Output100mACurrent - Quiescent (Iq)-Current - Supply (Max)-PSRR49dB (120Hz)Control Features-Protection FeaturesOver Temperature, Short CircuitOperating Temperature0°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Voltage - Input (Max)	-20V
Voltage Dropout (Max)1.7V @ 40mACurrent - Output100mACurrent - Quiescent (Iq)-Current - Supply (Max)-PSRR49dB (120Hz)Control Features-Protection FeaturesOver Temperature, Short CircuitOperating Temperature0°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Voltage - Output (Min/Fixed)	-5V
Current - Output100mACurrent - Quiescent (Iq)-Current - Supply (Max)-PSRR49dB (120Hz)Control Features-Protection FeaturesOver Temperature, Short CircuitOperating Temperature0°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Voltage - Output (Max)	-
Current - Quiescent (Iq)-Current - Supply (Max)-PSRR49dB (120Hz)Control Features-Protection FeaturesOver Temperature, Short CircuitOperating Temperature0°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Voltage Dropout (Max)	1.7V @ 40mA
Current - Supply (Max)-PSRR49dB (120Hz)Control Features-Protection FeaturesOver Temperature, Short CircuitOperating Temperature0°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Current - Output	100mA
PSRR49dB (120Hz)Control Features-Protection FeaturesOver Temperature, Short CircuitOperating Temperature0°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Current - Quiescent (Iq)	-
Control Features-Protection FeaturesOver Temperature, Short CircuitOperating Temperature0°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Current - Supply (Max)	-
Protection FeaturesOver Temperature, Short CircuitOperating Temperature0°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	PSRR	49dB (120Hz)
Operating Temperature0°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Control Features	-
Mounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Protection Features	Over Temperature, Short Circuit
Package / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Operating Temperature	0° C ~ 125°C
Supplier Device Package TO-92-3	Mounting Type	Through Hole
	Package / Case	TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)
Report errors?	Supplier Device Package	TO-92-3
		Report errors?

MC79L05ACLPME3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MC79L05ACLPME3 Payment Methods





If you have any question about MC79L05ACLPME3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com