

# ME20A2403N01

a Quote

#### ME20A2403N01 Information

Contraction of the second seco	Part Number	ME20A2403N01	
	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands	
	Category	Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters	- 337
	Description	AC/DC DESKTOP ADAPTER	- 9 <b>3</b> 547
	Package	-	- FEI - 40
For Reference Only		For the pricing/inventory/lead time, please contact	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# ME20A2403N01 Specifications

Manufacturer Part Number   ME20A2403N01     Manufacturer   SL Power Electronics Manufacture of Condor/Ault Brands     Category   Power Supplies - External/Internal (Off-Board)     AC DC Desktop, Wall Adapters   AC DC Desktop, Wall Adapters     Package   -     Series   ME20     Region Utilized   International     Form   Desktop (Class II)     Input Type   Cord (Sold Separately)     Voltage - Input   90 ~ 264VAC     Vourent - Output (Max)   830mA     Power (Watts)   20W     No Load Power Consumption   100mW (Max)     Polarization   Medical     Efficiency   Level VI     Operating Temperature   20°C ~ 70°C     Output Connector   Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm			
Category   Power Supplies - External/Internal (Off-Board)     AC DC Desktop, Wall Adapters     Package   -     Series   ME20     Region Utilized   International     Form   Desktop (Class II)     Input Type   Cord (Sold Separately)     Voltage - Input   90 ~ 264VAC     Voltage - Output   24V     Current - Output (Max)   830mA     Power (Watts)   20W     No Load Power Consumption   100mW (Max)     Applications   Accatel     Applications   Accatel     Operating Temperature   -0°C ~ 70°C     Output Connector   Bartel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	Manufacturer Part Number	ME20A2403N01	
AC DC Desktop, Wall AdaptersPackage-SeriesME20Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264VACVoltage - Output24VCurrent - Output (Max)830mAPower (Watts)00W(Max)No Load Power Consumption100mW (Max)PolarizationMedicalEfficiencyLevel VIOperating Temperature-20°C ~ 70°COutput Connector3.31" L x 1.85" W x 1.22" H (84.0mm x 47.0mm x 31.0mm)	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands	
Package.SeriesME20Region UtilizedInternationalFormDesktop Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output (Max)24VCurrent - Output (Max)830mAPower (Watts)00W (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VIOperating Temperature-20°C ~ 70°COutput ConnectorBartel Plug 2.5mm I.D.x. 5.5mm O.D.x. 9.5mmSize / Dimension3.31" x. x. 1.82" W. s. 2.2" H (84.0mm x. 47.0mm, s. 10.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series   ME20     Region Utilized   International     Form   Desktop (Class II)     Input Type   Cord (Sold Separately)     Voltage - Input   90 ~ 264VAC     Voltage - Output   24V     Current - Output (Max)   830mA     Power (Watts)   20W     No Load Power Consumption   100mW (Max)     Polarization   Positive Center     Applications   Kedical     Efficiency   Level VI     Operating Temperature   20°C ~ 70°C     Output Connector   Barrel Plug, 2.5mm I.D. x 5.5mm O.D.x 9.5mm     Size / Dimension   3.31" L x 1.85" W x 1.22" H (84.0mm x 47.0mm x 31.0mm)		AC DC Desktop, Wall Adapters	
Region UtilizedInternationalRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264VACVoltage - Output24VCurrent - Output (Max)830mAPower (Watts)20WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsKedicalEfficiencyLevel VIOperating Temperature-20°C ~ 70°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.22" H (84.0mm x 47.0mm x 31.0mm)	Package	-	
Form   Desktop (Class II)     Input Type   Cord (Sold Separately)     Voltage - Input   90 ~ 264VAC     Voltage - Output   24V     Current - Output (Max)   830mA     Power (Watts)   20W     No Load Power Consumption   100mW (Max)     Polarization   Positive Center     Applications   Medical     Efficiency   Level VI     Operating Temperature   20°C ~ 70°C     Output Connector   Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm     Size / Dimension   3.31" L x 1.85" W x 1.22" H (84.0mm x 47.0mm x 31.0mm)	Series	ME20	
Input Type   Cord (Sold Separately)     Voltage - Input   90 ~ 264VAC     Voltage - Output   24V     Current - Output (Max)   830mA     Power (Watts)   20W     No Load Power Consumption   100mW (Max)     Polarization   Positive Center     Applications   Medical     Efficiency   Level VI     Operating Temperature   -20°C ~ 70°C     Output Connector   Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm     Size / Dimension   3.31" L x 1.85" W x 1.22" H (84.0mm x 47.0mm x 31.0mm)	Region Utilized	International	
Voltage - Input   90 ~ 264VAC     Voltage - Output   24V     Current - Output (Max)   830mA     Power (Wats)   20W     No Load Power Consumption   100mW (Max)     Polarization   Positive Center     Applications   Medical     Efficiency   Level VI     Operating Temperature   20°C ~ 70°C     Output Connector   Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm     Size / Dimension   3.31" L x 1.85" W x 1.22" H (84.0mm x 47.0mm x 31.0mm)	Form	Desktop (Class II)	
Voltage - Output24VCurrent - Output (Max)830mAPower (Watts)20WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VIOperating Temperature-20°C ~ 70°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.22" H (84.0mm x 47.0mm x 31.0mm)	Input Type	Cord (Sold Separately)	
Current - Output (Max)830mAPower (Watts)20WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VIOperating Temperature-20°C ~ 70°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.22" H (84.0mm x 47.0mm x 31.0mm)	Voltage - Input	90 ~ 264VAC	
Power (Watts)20WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VIOperating Temperature-20°C ~ 70°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension.31" L x 1.85" W x 1.22" H (84.0mm x 47.0mm x 31.0mm)	Voltage - Output	24V	
No Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VIOperating Temperature-20°C ~ 70°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.22" H (84.0mm x 47.0mm x 31.0mm)	Current - Output (Max)	830mA	
PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VIOperating Temperature-20°C ~ 70°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.22" H (84.0mm x 47.0mm x 31.0mm)	Power (Watts)	20W	
ApplicationsMedicalEfficiencyLevel VIOperating Temperature-20°C ~ 70°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.22" H (84.0mm x 47.0mm x 31.0mm)	No Load Power Consumption	100mW (Max)	
EfficiencyLevel VIOperating Temperature-20°C ~ 70°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.22" H (84.0mm x 47.0mm x 31.0mm)	Polarization	Positive Center	
Operating Temperature-20°C ~ 70°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.31" L x 1.85" W x 1.22" H (84.0mm x 47.0mm x 31.0mm)	Applications	Medical	
Output Connector   Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm     Size / Dimension   3.31" L x 1.85" W x 1.22" H (84.0mm x 47.0mm x 31.0mm)	Efficiency	Level VI	
Size / Dimension 3.31" L x 1.85" W x 1.22" H (84.0mm x 47.0mm x 31.0mm)	Operating Temperature	-20°C ~ 70°C	
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	
Report error	Size / Dimension	3.31" L x 1.85" W x 1.22" H (84.0mm x 47.0mm x 31.0mm)	
1		Report errors?	

#### ME20A2403N01 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## ME20A2403N01 Payment Methods



### ME20A2403N01 Shipping Methods



If you have any question about ME20A2403N01, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com