

MENB1030A1503N01

MENB1030A1503N01 Information

Heisener.com	Part Number Manufacturer Category Description	MENB1030A1503N01 SL Power Electronics Manufacture of Condor/Ault Brands Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters AC/DC DESKTOP ADAPTER 15V 30W	
For Reference Only	Package	- For the pricing/inventory/lead time, please contact us	EI75327%
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MENB1030A1503N01 Specifications

Manufacturer Part NumberMENB 1030A 1503N01Manufacturer O Condor/Ault BrandsKategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesMENB 1030Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output15VCurrent - Output (Max)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsLevel VOperating Temperature-0°C ~ 40°COutput ConnectorBartel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesMENB1030Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output15VCurrent - Output (Max)2APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C	Manufacturer Part Number	MENB1030A1503N01
AC DC Desktop, Wall AdaptersPackage-SeriesMENB1030Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output (Max)2APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiency20°C ~ 40°C	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands
Package-SeriesMENB1030Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output15VCurrent - Output (Max)2APower (Watts)00mW (Max)No Load Power ConsumptionNoitwe CenterPolarizationMedicalApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C	Category	Power Supplies - External/Internal (Off-Board)
SeriesMENB1030Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output15VCurrent - Output (Max)2APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C		AC DC Desktop, Wall Adapters
Region UtilizedInternationalRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output15VCurrent - Output (Max)2APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C	Package	-
FormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output15VCurrent - Output (Max)2APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C	Series	MENB1030
Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output15VCurrent - Output (Max)2APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C	Region Utilized	International
Voltage - Input100 ~ 240 VACVoltage - Output15VCurrent - Output (Max)2APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C	Form	Desktop (Class II)
Voltage - Output15VCurrent - Output (Max)2APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C	Input Type	Cord (Sold Separately)
Current - Output (Max)2APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C	Voltage - Input	100 ~ 240 VAC
Power (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C	Voltage - Output	15V
No Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C	Current - Output (Max)	2A
PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C	Power (Watts)	30W
ApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C	No Load Power Consumption	100mW (Max)
EfficiencyLevel VOperating Temperature-20°C ~ 40°C	Polarization	Positive Center
Operating Temperature $-20^{\circ}\text{C} \sim 40^{\circ}\text{C}$	Applications	Medical
	Efficiency	Level V
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	Operating Temperature	$-20^{\circ}\text{C} \sim 40^{\circ}\text{C}$
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Size / Dimension 3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm)	Size / Dimension	3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm)
Report error		Report errors?

MENB1030A1503N01 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MENB1030A1503N01 Payment Methods



If you have any question about MENB1030A1503N01, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com