

**MJSU-24PL80 Information**


For Reference Only

**Part Number** [MJSU-24PL80](#)  
**Manufacturer** ITT Cannon, LLC  
**Category** Connectors, Interconnects  
[Rectangular Connectors - Headers, Male Pins](#)  
**Description** MICRO  
**Package** -  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)


[Request a Quote](#)
**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**MJSU-24PL80 Specifications**

|                            |  |
|----------------------------|--|
| Manufacturer Part Number   | <a href="#">MJSU-24PL80</a>  |
| Manufacturer               | ITT Cannon, LLC  |
| Category                   | Connectors, Interconnects<br><a href="#">Rectangular Connectors - Headers, Male Pins</a> |
| Package                    | -  |
| Series                     | MJS  |
| Connector Type             | Header   |
| Contact Type               | Male Pin   |
| Pitch - Mating             | -  |
| Style                      | Board to Cable/Wire  |
| Shrouding                  | Unshrouded   |
| Number of Positions        | 24   |
| Number of Positions Loaded | All  |
| Number of Rows             | 3  |
| Row Spacing - Mating       | -  |
| Mounting Type              | Through Hole   |
| Termination                | Solder   |
| Fastening Type             | Threaded   |
| Contact Length - Mating    | -  |
| Contact Length - Post      | -  |
| Overall Contact Length     | -  |
| Insulation Height          | 0.170" (4.32mm)  |
| Contact Shape              | Circular   |
| Contact Finish - Mating    | Gold   |

|                                   |                      |
|-----------------------------------|----------------------|
| Contact Finish Thickness - Mating | 50μin (1.27μm)       |
| Contact Finish - Post             | -                    |
| Contact Material                  | Copper Alloy         |
| Insulation Material               | Polyetherimide (PEI) |
| Features                          | -                    |
| Operating Temperature             | -55°C ~ 125°C        |
| Ingress Protection                | -                    |
| Material Flammability Rating      | -                    |
| Insulation Color                  | Natural              |
| <a href="#">Report errors?</a>    |                      |

## MJSU-24PL80 Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MJSU-24PL80 Payment Methods



## MJSU-24PL80 Shipping Methods



If you have any question about MJSU-24PL80, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)