

MK2P-S-AC240 Information

Heisener.com

Part Number MK2P-S-AC240

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 10A 240V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MK2P-S-AC240 Specifications

Manufacturer MK2P-S-AC240 Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series MK Relay Type General Purpose Coil Type Non Latching Coil Current 9.2mA Coil Voltage 240VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)		
Category Relays Power Relays, Over 2 Amps Package - Series MK Relay Type General Purpose Coil Type Non Latching Coil Current 9.2mA Coil Voltage 240VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator, Test Button Mounting Type Fermination Style Pug In, 8 Pin (Octal)	Manufacturer Part Number	MK2P-S-AC240
Package-SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.2mACoil Voltage240VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesMechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, 8 Pin (Octal)	Manufacturer	Omron Automation and Safety
Package-SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.2mACoil Voltage240VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesMechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, 8 Pin (Octal)	Category	Relays
SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.2mACoil Voltage240VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesMechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, 8 Pin (Octal)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 9.2mA Coil Voltage 240VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Release Time 20ms Features Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Package	-
Coil Type Non Latching Coil Current 9.2mA Coil Voltage 240VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Series	MK
Coil Current9.2mACoil Voltage240VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesMechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, 8 Pin (Octal)	Relay Type	General Purpose
Coil Voltage 240VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Coil Current	9.2mA
Contact Rating (Current) Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Coil Voltage	240VAC
Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Contact Rating (Current)	10A
Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Switching Voltage	250VAC, 250VDC - Max
Operate Time 20ms Release Time 20ms Features Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Turn On Voltage (Max)	192 VAC
Release Time 20ms Features Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Turn Off Voltage (Min)	72 VAC
Features Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Release Time	20ms
Termination Style Plug In, 8 Pin (Octal)	Features	Mechanical Indicator, Test Button
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, 8 Pin (Octal)
· ·		Report errors?

MK2P-S-AC240 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MK2P-S-AC240 Payment Methods



















MK2P-S-AC240 Shipping Methods













If you have any question about MK2P-S-AC240, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com