



MKJ3B6F6-4SN Information



For Reference Only

Part NumberMKJ3B6F6-4SNManufacturerITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

Description CONN PLUG 4POS STRGHT W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MKJ3B6F6-4SN Specifications

Manufacturer Part Number MKJ3B6F6-4SN Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-38999, MKJ3 Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 6-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-38999, MKJ3 Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 6-4 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Current Rating 5A	Manufacturer Part Number	MKJ3B6F6-4SN
Circular Connectors Package - Series MIL-DTL-38999, MKJ3 Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 6-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Current Rating 5A	Manufacturer	ITT Cannon, LLC
Package - Series MIL-DTL-38999, MKJ3 Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 6-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5	Category	Connectors, Interconnects
Series MIL-DTL-38999, MKJ3 Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 6-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A		Circular Connectors
Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 6-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Package	-
Number of Positions Shell Size - Insert 6-4 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Series	MIL-DTL-38999, MKJ3
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Features Shielded Voltage - Rated Current Rating 5A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Current Rating 5A	Number of Positions	4
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Shell Size - Insert	6-4
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Aluminum Alloy, Nickel Plated, Electroless Gold Shielded Shielded 500VAC	Orientation	N (Normal)
Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated 500VAC Current Rating 5A	Shell Material, Finish	Aluminum Alloy, Nickel Plated, Electroless
Voltage - Rated 500VAC Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	Shielded
-	Voltage - Rated	500VAC
Report errors?	Current Rating	5A
		Report errors?

MKJ3B6F6-4SN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MKJ3B6F6-4SN Payment Methods



















MKJ3B6F6-4SN Shipping Methods













If you have any question about MKJ3B6F6-4SN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com