

MKP1839415134HQG

MKP1839415134HQG Information

Part Number MKP1839415134HQG
Manufacturer Vishay BC Components

Category Capacitors Film Capacitors

Description CAP FILM 0.15UF 5% 1.6KVDC AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

www.heisener.com

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MKP1839415134HQG Specifications

SeriesMKP1839 HQCapacitance0.15μFTolerance±5%Voltage Rating - AC450VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.551" Dia x 1.240" L (14.00mm x 31.50mm)Height - Seated (Max)-TerminationPC PinsLead Spacing-ApplicationsHigh Pulse, DV/DTFeatures-		
Category Capacitors Package Axial Series MKP1839 HQ Capacitance 0.15µF Tolerance ±5% Voltage Rating - AC 450V Voltage Rating - DC 1600V (1.6kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Axial Size / Dimension 0.551" Dia x 1.240" L (14.00mm x 31.50mm) Height - Seated (Max) - Termination PC Pins Lead Spacing - Applications High Pulse, DV/DT Features -	Manufacturer Part Number	MKP1839415134HQG
Film Capacitors Axial Series MKP1839 HQ Capacitance 0.15µF Tolerance ±5% Voltage Rating - AC Voltage Rating - DC Dielectric Material ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) - Termination PC Pins Lead Spacing - Applications High Pulse, DV/DT Features	Manufacturer	Vishay BC Components
PackageAxialSeriesMKP1839 HQCapacitance0.15µFTolerance±5%Voltage Rating - AC450VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.551" Dia x 1.240" L (14.00mm x 31.50mm)Height - Seated (Max)-TerminationPC PinsLead Spacing-ApplicationsHigh Pulse, DV/DTFeatures-	Category	Capacitors
Series MKP1839 HQ Capacitance 0.15μF Tolerance ±5% Voltage Rating - AC 450V Voltage Rating - DC 1600V (1.6kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Axial Size / Dimension 0.551" Dia x 1.240" L (14.00mm x 31.50mm) Height - Seated (Max) - Termination PC Pins Lead Spacing - Applications High Pulse, DV/DT Features -		Film Capacitors
Capacitance 0.15µF Tolerance ±5% Voltage Rating - AC 450V Voltage Rating - DC 1600V (1.6kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Axial Size / Dimension 0.551" Dia x 1.240" L (14.00mm x 31.50mm) Height - Seated (Max) - Termination PC Pins Lead Spacing - Applications High Pulse, DV/DT Features -	Package	Axial
Tolerance ±5% Voltage Rating - AC 450V Voltage Rating - DC 1600V (1.6kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Axial Size / Dimension 0.551" Dia x 1.240" L (14.00mm x 31.50mm) Height - Seated (Max) - Termination PC Pins Lead Spacing - Applications High Pulse, DV/DT Features -	Series	MKP1839 HQ
Voltage Rating - AC Voltage Rating - DC 1600V (1.6kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) - Termination PC Pins Lead Spacing Applications High Pulse, DV/DT Features - 450V 450V 450V 1600V (1.6kV) Polypropylene (PP), Metallized - 1600V (1.6kV) Polypropylene (PP), Metallized 1600V (1.6kV) Polypropylene (PP), Metallized - 1600V (1.6kV) Polypropylene (PP), Metallized - 1600V (1.6kV) - 1600V (1.	Capacitance	0.15μF
Voltage Rating - DC Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Axial Size / Dimension 0.551" Dia x 1.240" L (14.00mm x 31.50mm) Height - Seated (Max) - Termination PC Pins Lead Spacing Applications High Pulse, DV/DT Features -	Tolerance	±5%
Dielectric Material ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Termination Lead Spacing Applications Polypropylene (PP), Metallized - 0.55°C ~ 110°C Through Hole Axial 0.551" Dia x 1.240" L (14.00mm x 31.50mm) - 0.551" Dia x 1.240" L (14.00mm x 31.50mm) High Pulse, DV/DT Features - 0.551" Dia x 1.240" L (14.00mm x 31.50mm)	Voltage Rating - AC	450V
ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Termination PC Pins Lead Spacing - Applications High Pulse, DV/DT Features - S5°C ~ 110°C Through Hole -55°C ~ 110°C Through Hole -55°C ~ 110°C -55°C ~ 110°	Voltage Rating - DC	1600V (1.6kV)
Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Axial Size / Dimension 0.551" Dia x 1.240" L (14.00mm x 31.50mm) Height - Seated (Max) - Termination PC Pins Lead Spacing - Applications High Pulse, DV/DT Features -	Dielectric Material	Polypropylene (PP), Metallized
Mounting Type Through Hole Package / Case Axial Size / Dimension 0.551" Dia x 1.240" L (14.00mm x 31.50mm) Height - Seated (Max) - Termination PC Pins Lead Spacing - Applications High Pulse, DV/DT Features -	ESR (Equivalent Series Resistance)	-
Package / Case Axial Size / Dimension 0.551" Dia x 1.240" L (14.00mm x 31.50mm) Height - Seated (Max) - Termination PC Pins Lead Spacing - Applications High Pulse, DV/DT Features -	Operating Temperature	-55°C ~ 110°C
Size / Dimension 0.551" Dia x 1.240" L (14.00mm x 31.50mm) Height - Seated (Max) - Termination PC Pins Lead Spacing - Applications High Pulse, DV/DT Features -	Mounting Type	Through Hole
Height - Seated (Max) Termination PC Pins Lead Spacing - Applications High Pulse, DV/DT Features -	Package / Case	Axial
Termination PC Pins Lead Spacing - Applications High Pulse, DV/DT Features -	Size / Dimension	0.551" Dia x 1.240" L (14.00mm x 31.50mm)
Lead Spacing - Applications High Pulse, DV/DT Features -	Height - Seated (Max)	-
Applications High Pulse, DV/DT Features -	Termination	PC Pins
Features -	Lead Spacing	-
	Applications	High Pulse, DV/DT
Report errors	Features	-
Report circles		Report errors

MKP1839415134HQG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MKP1839415134HQG Payment Methods



















MKP1839415134HQG Shipping Methods













If you have any question about MKP1839415134HQG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com