

MKP383316250JKP2T0

MKP383316250JKP2T0 Information

| Contraction Com Distant Network Contractions | Part Number Manufacturer Category Description Package | MKP383316250JKP2T0 Vishay BC Components Capacitors Film Capacitors CAP FILM 0.016UF 5% 2.5KVDC RAD Radial For the pricing/inventory/lead time, please contact | |
|---|---|---|-----------------|
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP383316250JKP2T0 Specifications

| Manufacturer Part NumberMKP383316250JKP2T0ManufacturerVishay BC ComponentsCategoryCapacitorsPackageRadialSeriesMMKP383Capacitance0.016µFTolerance±5%Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Dielectric MaterialPolypropylene (PP), MetallizedSeries-Operating Temperature-55°C ~ 105°CMounting TypeThrough HoleSize / Dimension1.240" L x 0.354" W (31.50mm x 9.00mm)Height - Seated (Max)0.748" (19.00mm)Lead Spacing6.6eeral Purpose | | |
|---|------------------------------------|--|
| CategoryCapacitorsFilm CapacitorsPackageRadialSeriesMMKP383Capacitance0.016µFTolerance±5%Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Dielectric MaterialPolypropulene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HoleSize / Dimension1.240° L x 0.354" W (31.50mm x 9.00mm)Height - Seated (Max)0.748" (19.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsGeneral Purpose | Manufacturer Part Number | MKP383316250JKP2T0 |
| Film CapacitorsPackageRadialSeriesMMKP383Capacitance0.016µFTolerance±5%Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeRadialSize / Dimension1.240" L x 0.354" W (31.50mm x 9.00mm)Height - Seated (Max)0.748" (19.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsGeneral Purpose | Manufacturer | Vishay BC Components |
| PackageRadialSeriesMMKP383Capacitance0.016µFTolerance±5%Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Dielectric MaterialPolypropelne (PP), MetallizedDielectric Material-Operating Temperature55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.354" W (31.50mm x 9.00mm)Height - Seated (Max)O7 HasLead Spacing1.083" (27.50mm)ApplicationsGeneral Purpose | Category | Capacitors |
| SeriesMMKP383Capacitance0.016µFTolerance±5%Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.354" W (31.50mm x 9.00mm)Height - Seated (Max)O748" (19.00mm)Lead Spacing1.083" (27.50mm)ApplicationsGeneral Purpose | | Film Capacitors |
| Capacitance0.016µFTolerance±5%Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension1.240" L x 0.354" W (31.50mm x 9.00mm)Height - Seated (Max)0.748" (19.00mm)Lead Spacing1.083" (27.50mm)ApplicationsGeneral Purpose | Package | Radial |
| Tolerance±5%Yoltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240° L x 0.354" W (31.50mm x 9.00mm)Height - Seated (Max)Or 748" (19.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsGeneral Purpose | Series | MMKP383 |
| Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240° L x 0.354" W (31.50mm x 9.00mm)Height - Seated (Max)PC PinsTerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsGeneral Purpose | Capacitance | 0.016µF |
| Voltage Rating - DC2500V (2.5kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.354" W (31.50mm x 9.00mm)Height - Seated (Max)0.748" (19.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsGeneral Purpose | Tolerance | $\pm 5\%$ |
| Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.354" W (31.50mm x 9.00mm)Height - Seated (Max)0.748" (19.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsGeneral Purpose | Voltage Rating - AC | 900V |
| ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.354" W (31.50mm x 9.00mm)Height - Seated (Max)0.748" (19.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsGeneral Purpose | Voltage Rating - DC | 2500V (2.5kV) |
| Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.354" W (31.50mm x 9.00mm)Height - Seated (Max)0.748" (19.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsGeneral Purpose | Dielectric Material | Polypropylene (PP), Metallized |
| Nounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.354" W (31.50mm x 9.00mm)Height - Seated (Max)0.748" (19.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsGeneral Purpose | ESR (Equivalent Series Resistance) | - |
| Package / CaseRadialSize / Dimension1.240" L x 0.354" W (31.50mm x 9.00mm)Height - Seated (Max)0.748" (19.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsGeneral Purpose | Operating Temperature | -55°C ~ 105°C |
| Size / Dimension1.240" L x 0.354" W (31.50mm x 9.00mm)Height - Seated (Max)0.748" (19.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsGeneral Purpose | Mounting Type | Through Hole |
| Height - Seated (Max)0.748" (19.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsGeneral Purpose | Package / Case | Radial |
| TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsGeneral Purpose | Size / Dimension | 1.240" L x 0.354" W (31.50mm x 9.00mm) |
| Lead Spacing1.083" (27.50mm)ApplicationsGeneral Purpose | Height - Seated (Max) | 0.748" (19.00mm) |
| Applications General Purpose | Termination | PC Pins |
| | Lead Spacing | 1.083" (27.50mm) |
| Easterna | Applications | General Purpose |
| reatures - | Features | - |
| Report errors | | Report errors? |

MKP383316250JKP2T0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

S MoneyGram Alipay VISA

DISCOVER

MKP383316250JKP2T0 Payment Methods



MKP383316250JKP2T0 Shipping Methods



If you have any question about MKP383316250JKP2T0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com