

MLS283M5R0EA0D

MLS283M5R0EA0D Information



For Reference Only

Part Number	MLS283M5R0EA0D	
Manufacturer	Cornell Dubilier Electronics (CDE)	
Category	Capacitors Aluminum Electrolytic Capacitors	
Description	CAP ALUM 28000UF 20% 5V FLATPACK	
Package	FlatPack, Tabbed	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MLS283M5R0EA0D Specifications

Manufacturer Part NumberMLS283M5R0EA0DManufacturerCornell Dubilier Electronics (CDE)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageFlatPack, TabbedStriesMLSCopacitance28000µFTolerance±20%Voltage - Rated50ESR (Equivalent Series Resistance)50 mOhn @ 120HzLifetime @ Temp.0000 Hrs @ 85°COperating Temperature50°C ~ 125°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.44 @ 20kHzImpedance.Lidad Spacing3000° 12.71.70°W (50.80mm x 44.45mm)Bight - Saate (Max)0.300° 12.70mm)Surface Mount Land Size.Mounting TypeHatPack, TabbedPolarize Mount Land Size.Package (CaseFlatPack, Tabbed		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageFlatPack, TabbedSeriesMLSCapacitance2800µFTolerance±20%Voltage - Rated5VESR (Equivalent Series Resistance)50 mOhm @ 120HzDiperating Temperature10000 Hrs @ 85°COperating Temperature90arApplicationsGeneral PurposeRipple Current - High Frequency19.9A @ 120HzNipple Current - High Frequency1.4A @ 20kHzImpedance-Lead Spacing1.000" (25.40mm)Size / Dimension2.000" L x 1.750" W (50.80mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeChasis MountPackage / CaseFlatPack, Tabbed	Manufacturer Part Number	MLS283M5R0EA0D
Adminum Electrolytic CapacitorsPackageFlatPack, TabbedSeriesMLSCapacitance28000µFTolerance±20%Voltage - Rated5VESR (Equivalent Series Resistance)50 mOhm @ 120HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature55°C ~ 125°CPolarizationGeneral PurposeRipple Current - Low Frequency19.9A @ 120HzRipple Current - High Frequency21.4A @ 20kHzImpedance-Lead Spacing3.000° Lx 1.750° W (50.80mm x 44.45mm)Size / Dimension0.500° (12.70mm)Surface Mount Land Size-Mounting TypeFlatPack, TabbedPackage / CaseFlatPack, Tabbed	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageFlatPack, TabbedSeriesMLSCapacitance28000µFTolerance±20%Voltage - Rated5VESR (Equivalent Series Resistance)50 mOhm @ 120HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature55°C ~ 125°CPolarizationGeneral PurposeRipple Current - Low Frequency9.9A @ 120HzRipple Current - High Frequency1.000° (25.40mm)Size / Dimension2.000° L x 1.750° W (50.80mm x 44.45mm)Size / Dimension5.00° (12.70mm)Surface Mount Land Size-Mounting TypeFlatPack, Tabbed	Category	Capacitors
SeriesMLSCapacitance2800µFTolerance±20%Voltage - Rated5VESR (Equivalent Series Resistance)50 mOhm @ 120HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-55°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency19.9A @ 120HzImpedance-Lead Spacing1.000° (25.40mm)Size / Dinension0.500° (12.70mm)Surface Mount Land Size-Mounting TypeChasis MountPokage / CaseFlatPack, Tabbed		Aluminum Electrolytic Capacitors
Capacitance2800µFTolerance±20%Voltage Rated5VESR (Equivalent Series Resistance)50 mOhm @ 120HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature>55°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Hoy Frequency19.9A @ 120HzImpedance-Lead Spacing1.000" (25.40mm)Size / Dimension2.000" L x 1.750" W (50.80mm x 44.45mm)Surface Mount Land Size-Mounting TypeChasis MountPackage / CaseFlatPack, Tabbed	Package	FlatPack, Tabbed
Tolerance±20%Voltage - Rated5VESR (Equivalent Series Resistance)50 mOhm @ 120HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-55°C ~ 125°CPolarzationPolarApplicationsGeneral PurposeRipple Current - Low Frequency19.9A @ 120HzImpedance-Lead Spacing1.000" (25.40mm)Size / Dimension0.500" (12.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseFlatPack, Tabbed	Series	MLS
Voltage - Rated5VESR (Equivalent Series Resistance)50 mOhm @ 120HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-55°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency19.9A @ 120HzRipple Current - High Frequency21.4A @ 20kHzImpedance-Lead Spacing1.000" (25.40mm)Size / Dimension0.500" (12.70mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Pounting TypeFatPack, Tabbed	Capacitance	28000µF
ESR (Equivalent Series Resistance) 50 mOhm @ 120Hz ESR (Equivalent Series Resistance) 50 mOhm @ 120Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -55°C ~ 125°C Polar Polar Applications General Purpose Ripple Current - Low Frequency 19.9A @ 120Hz Impedance - Lead Spacing 1.000" (25.40mm) Size / Dimension 2.000" L x 1.750" W (50.80mm x 44.45mm) Height - Seated (Max) 0.500" (12.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case FlatPack, Tabbed	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°CDeprating Temperature-55°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency19.9A @ 120HzRipple Current - High Frequency21.4A @ 20kHzImpedance-Lead Spacing1.000" (25.40mm)Size / Dimension0.500" (12.70mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseFlatPack, Tabbed	Voltage - Rated	5V
Operating Temperature -55°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 19.9A @ 120Hz Ripple Current - High Frequency 21.4A @ 20kHz Impedance - Lead Spacing 1.000" (25.40mm) Size / Dimension 2.000" L x 1.750" W (50.80mm x 44.45mm) Height - Seated (Max) 0.500" (12.70mm) Surface Mount Land Size - Mounting Type Chasis Mount FlatPack, Tabbed FlatPack, Tabbed	ESR (Equivalent Series Resistance)	50 mOhm @ 120Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency19.9A @ 120HzRipple Current - High Frequency21.4A @ 20kHzImpedance-Lead Spacing1.000" (25.40mm)Size / Dimension2.000" L x 1.750" W (50.80mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseFlatPack, Tabbed	Lifetime @ Temp.	10000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 19.9A @ 120Hz Ripple Current - High Frequency 21.4A @ 20kHz Impedance - Lead Spacing 1.000" (25.40mm) Size / Dimension 2.000" L x 1.750" W (50.80mm x 44.45mm) Height - Seated (Max) 0.500" (12.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case FlatPack, Tabbed	Operating Temperature	-55°C ~ 125°C
Ripple Current - Low Frequency 19.9A @ 120Hz Ripple Current - High Frequency 21.4A @ 20kHz Impedance - Lead Spacing 1.000" (25.40mm) Size / Dimension 2.000" L x 1.750" W (50.80mm x 44.45mm) Height - Seated (Max) 0.500" (12.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case FlatPack, Tabbed	Polarization	Polar
Ripple Current - High Frequency21.4A @ 20kHzImpedance-Lead Spacing1.000" (25.40mm)Size / Dimension2.000" L x 1.750" W (50.80mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseFlatPack, Tabbed	Applications	General Purpose
Impedance-Lead Spacing1.000" (25.40mm)Size / Dimension2.000" L x 1.750" W (50.80mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseFlatPack, Tabbed	Ripple Current - Low Frequency	19.9A @ 120Hz
Lead Spacing 1.000" (25.40mm) Size / Dimension 2.000" L x 1.750" W (50.80mm x 44.45mm) Height - Seated (Max) 0.500" (12.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case FlatPack, Tabbed	Ripple Current - High Frequency	21.4A @ 20kHz
Size / Dimension2.000" L x 1.750" W (50.80mm x 44.45mm)Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseFlatPack, Tabbed	Impedance	-
Height - Seated (Max)0.500" (12.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseFlatPack, Tabbed	Lead Spacing	1.000" (25.40mm)
Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseFlatPack, Tabbed	Size / Dimension	2.000" L x 1.750" W (50.80mm x 44.45mm)
Mounting TypeChassis MountPackage / CaseFlatPack, Tabbed	Height - Seated (Max)	0.500" (12.70mm)
Package / Case FlatPack, Tabbed	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	FlatPack, Tabbed
		Report errors?

MLS283M5R0EA0D Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MLS283M5R0EA0D Payment Methods





If you have any question about MLS283M5R0EA0D, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com