

MPB80-3000 Information



For Reference Only

Part Number MPB80-3000

Manufacturer Bel Power Solutions

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 5V +/-12V 80W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MPB80-3000 Specifications

Manufacturer Part Number MPB80-3000 Manufacturer Bel Power Solutions Category Power Supplies - External/Internal (Off-Board) Package - Series MPB80 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 7A, 2.5A, 300mA Power (Watts) 80W Applications ITE (Commercial) Voltage - Isolation 2.6kV (2600V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	•	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series MPB80 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 7A, 2.5A, 300mA Power (Watts) 80W Applications ITE (Commercial) Voltage - Isolation 2.6kV (2600V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Manufacturer Part Number	MPB80-3000
Package - Series MPB80 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 7A, 2.5A, 300mA Power (Watts) 80W Applications ITE (Commercial) Voltage - Isolation 2.6kV (2600V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Manufacturer	Bel Power Solutions
Package - Series MPB80 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 7A, 2.5A, 300mA Power (Watts) 80W Applications ITE (Commercial) Voltage - Isolation 2.6kV (2600V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Category	Power Supplies - External/Internal (Off-Board)
Series MPB80 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 7A, 2.5A, 300mA Power (Watts) 80W Applications ITE (Commercial) Voltage - Isolation 2.6kV (2600V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)		AC DC Converters
Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 7A, 2.5A, 300mA Power (Watts) 80W Applications ITE (Commercial) Voltage - Isolation 2.6kV (2600V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Package	-
Number of Outputs3Voltage - Input $85 \sim 264 \text{ VAC}$ Voltage - Output 1 $5V$ Voltage - Output 2 $12V$ Voltage - Output 3 $-12V$ Voltage - Output 4-Current - Output (Max) $7A, 2.5A, 300\text{mA}$ Power (Watts) $80W$ ApplicationsITE (Commercial)Voltage - Isolation $2.6\text{kV} (2600\text{V})$ Efficiency 73% Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C} \text{ (With Derating)}$ FeaturesAdjustable Output, PFC, Universal InputMounting TypeChassis MountSize / Dimension $5.00^{\circ}\text{L x } 3.00^{\circ}\text{W x } 1.40^{\circ}\text{H } (127.0\text{mm x } 76.2\text{mm x } 35.6\text{mm})$	Series	MPB80
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) 7A, 2.5A, 300mA Power (Watts) 80W Applications ITE (Commercial) Voltage - Isolation 2.6kV (2600V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Type	Open Frame
Voltage - Output 1 Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 2.6kV (2600V) Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Number of Outputs	3
Voltage - Output 2 Voltage - Output 3 -12V Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 2.6kV (2600V) Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 12V 12V 12V 12V 12V 12V 12V 12	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 2.6kV (2600V) Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension -12V -	Voltage - Output 1	5V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 2.6kV (2600V) Efficiency 73% Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension	Voltage - Output 2	12V
Current - Output (Max) Power (Watts) 80W Applications ITE (Commercial) Voltage - Isolation 2.6kV (2600V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7A, 2.5A, 300mA 80W AU AU Commercial) Commercial Commercial Au Commercial Commercial Commercial Commercial Au Commercial	Voltage - Output 3	-12V
Power (Watts)80WApplicationsITE (Commercial)Voltage - Isolation2.6kV (2600V)Efficiency73%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 2.6kV (2600V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Current - Output (Max)	7A, 2.5A, 300mA
Voltage - Isolation 2.6kV (2600V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Power (Watts)	80W
Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Applications	ITE (Commercial)
Operating Temperature 0°C ~ 70°C (With Derating) Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Voltage - Isolation	2.6kV (2600V)
Features Adjustable Output, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Efficiency	73%
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Operating Temperature	0°C ~ 70°C (With Derating)
Size / Dimension 5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)	Features	Adjustable Output, PFC, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.40" H (127.0mm x 76.2mm x 35.6mm)
		Report errors?

MPB80-3000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MPB80-3000 Payment Methods



















MPB80-3000 Shipping Methods













If you have any question about MPB80-3000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com