



MPC3RTW12.0 Information

Heisener.com

Part Number MPC3RTW12.0

Manufacturer Bivar Inc.

Category Optoelectronics

Panel Indicators, Pilot Lights

Description LED PANEL INDICATOR RED 2.1V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MPC3RTW12.0 Specifications

Manufacturer MPC3RTW12.0 Manufacturer Bivar Inc. Category Optoelectronics Panel Indicators, Pilot Lights Package - Series MPC3 Type LED Lamp Color Red Lens Color Red Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 2.1V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.24" (6.10mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 2.5mcd Wavelength - Peak 700nm Viewing Angle 20° Termination Style Wire Leads - 12" (304.80mm) Ingress Protection - Features -		
Category Panel Indicators, Pilot Lights Package Packag	Manufacturer Part Number	MPC3RTW12.0
Package-SeriesMPC3TypeLEDLamp ColorRedLens TransparencyClearRatingsVf (Typ), If (Max)Voltage2.1VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.24" (6.10mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating2.5mcdWavelength - Peak700nmViewing Angle20°Termination StyleWire Leads - 12" (304.80mm)Ingress Protection-Features-	Manufacturer	Bivar Inc.
Package - Series MPC3 Type LED Lamp Color Red Lens Color Red Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 2.1V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.24" (6.10mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 2.5mcd Wavelength - Peak 700nm Viewing Angle 20° Termination Style Wire Leads - 12" (304.80mm) Ingress Protection - Features -	Category	Optoelectronics
Series MPC3 Type LED Lamp Color Red Lens Color Red Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 2.1V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.24" (6.10mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 2.5mcd Wavelength - Peak 700nm Viewing Angle 20° Termination Style Wire Leads - 12" (304.80mm) Ingress Protection - Features -		Panel Indicators, Pilot Lights
TypeLEDLamp ColorRedLens ColorRedLens TransparencyClearRatingsVf (Typ), If (Max)Voltage2.1VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.24" (6.10mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating2.5mcdWavelength - Peak700nmViewing Angle20°Termination StyleWire Leads - 12" (304.80mm)Ingress Protection-Features-	Package	-
Lamp Color Lens Color Red Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 2.1V Current 20mA Panel Cutout Shape Ranel Cutout Dimensions Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 2.5mcd Wavelength - Peak 700nm Viewing Angle 20° Termination Style Ingress Protection Features Red Wed Red Red Red Red Red Red Red Red Red R	Series	MPC3
Lens ColorRedLens TransparencyClearRatingsVf (Typ), If (Max)Voltage2.1VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.24" (6.10mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating2.5mcdWavelength - Peak700nmViewing Angle20°Termination StyleWire Leads - 12" (304.80mm)Ingress Protection-Features-	Type	LED
Lens TransparencyClearRatingsVf (Typ), If (Max)Voltage2.1VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.24" (6.10mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating2.5mcdWavelength - Peak700nmViewing Angle20°Termination StyleWire Leads - 12" (304.80mm)Ingress Protection-Features-	Lamp Color	Red
RatingsVf (Typ), If (Max)Voltage2.1VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.24" (6.10mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating2.5mcdWavelength - Peak700nmViewing Angle20°Termination StyleWire Leads - 12" (304.80mm)Ingress Protection-Features-	Lens Color	Red
Voltage 2.1V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.24" (6.10mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 2.5mcd Wavelength - Peak 700nm Viewing Angle 20° Termination Style Wire Leads - 12" (304.80mm) Ingress Protection - Features -	Lens Transparency	Clear
Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.24" (6.10mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 2.5mcd Wavelength - Peak 700nm Viewing Angle 20° Termination Style Wire Leads - 12" (304.80mm) Ingress Protection - Features -	Ratings	Vf (Typ), If (Max)
Panel Cutout Shape Round Panel Cutout Dimensions 0.24" (6.10mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 2.5mcd Wavelength - Peak 700nm Viewing Angle 20° Termination Style Wire Leads - 12" (304.80mm) Ingress Protection - Features -	Voltage	2.1V
Panel Cutout Dimensions 0.24" (6.10mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 2.5mcd Wavelength - Peak 700nm Viewing Angle 20° Termination Style Wire Leads - 12" (304.80mm) Ingress Protection - Features -	Current	20mA
Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating2.5mcdWavelength - Peak700nmViewing Angle20°Termination StyleWire Leads - 12" (304.80mm)Ingress Protection-Features-	Panel Cutout Shape	Round
Millicandela Rating 2.5mcd Wavelength - Peak 700nm Viewing Angle 20° Termination Style Wire Leads - 12" (304.80mm) Ingress Protection Features -	Panel Cutout Dimensions	0.24" (6.10mm)
Wavelength - Peak 700nm Viewing Angle 20° Termination Style Wire Leads - 12" (304.80mm) Ingress Protection - Features -	Lens Style/Size	Round with Domed Top, 3mm (T-1)
Viewing Angle20°Termination StyleWire Leads - 12" (304.80mm)Ingress Protection-Features-	Millicandela Rating	2.5mcd
Termination Style Wire Leads - 12" (304.80mm) Ingress Protection - Features -	Wavelength - Peak	700nm
Ingress Protection - Features -	Viewing Angle	20°
Features -	Termination Style	Wire Leads - 12" (304.80mm)
	Ingress Protection	-
Report errors?	Features	-
i i		Report errors?

MPC3RTW12.0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MPC3RTW12.0 Payment Methods



















MPC3RTW12.0 Shipping Methods













If you have any question about MPC3RTW12.0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com