

MPI001/TE/GN/24

MPI001/TE/GN/24 Information

Contract levels cards been	Part Number Manufacturer Category Description Package	MPI001/TE/GN/24 Bulgin Switches Pushbutton Switches SWITCH PUSH SPST-NO 0.05A 24V - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MPI001/TE/GN/24 Specifications

Manufacturer Part Number MPI001/TE/GN/24 Manufacturer Bulgin Category Switches Package - Package - Series - Type Vandal Resistant, Illuminated Circuit SPST-NO Switch Function Off-Mom Current Rating SomA (DC) Voltage Rating - AC - Voltage Rating - DC Acudal Button, Flush Color - Actuator/Cap Silver Illumination Type, Color ED, Green Illumination Voltage (Nominal) AVDC Mounting Type Screw Terminal Ingress Protection Screw Terminal Ingress Protection Stailess Steel Panel Mount, Fingth, Water Resistant Sceport errors;		
CategorySwitchesPackage-Series-TypeVandal Resistant, IlluminatedCircuitSPST-NOSwitch FunctionOff-MomCurrent RatingOff-MomVoltage Rating - AC-Voltage Rating - DC24VActuator TypeSilverClor - Actuator/CapSilverIllumination Voltage (Nominal)24 VDCMunting TypePanel Mount, FrontIllumination SyleScrew TerminalIngress ProtectionProfe - Dust Tight, Water ResistantFeaturesNond StelelPanel Cutout DimensionsCircular - 19.20mm Dia	Manufacturer Part Number	MPI001/TE/GN/24
PackagePushbuton SwitchesPackage-Series-TypeVandal Resistant, IlluminatedCircuitSPST-NOSwitch FunctionOff-MomCurrent RatingS0mA (DC)Voltage Rating - AC-Voltage Rating - DC24VActuator TypeRound, Button, FlushColor - Actuator/CapSilverIllumination Voltage (Nominal)24 VDCMounting TypePanel Mount, FrontTermination StyleScrew TerminalIngress ProtectionIE66 - Dust Tight, Water ResistantFeaturesStailess SteelPanel Cutout DimensionsCircular - 19.20mm Dia	Manufacturer	Bulgin
Package.Series.TypeVanda Resistant, IlluminatedTypeSPST-NOSwitch FunctionOff-MornSwitch FunctionSomA (DC)Current Rating.Voltage Rating - AC.Voltage Rating - DCAdvantant (Suman)Actuator TypeRound, Button, FlushColor - Actuator/CapSilverIllumination Voltage (Nominal)ActOCMounting TypePanel Mount, FrontIngress ProtectionSicwa TerminalIngress ProtectionPG6 - Dust Tight, Water ResistantFeaturesStainless SteelAnel Cutout DimensionsCircular - 19.20m Dia	Category	Switches
Series.TypeVanda Resistant, IlluminatedCircuitSPST-NOSwitch FunctionOff-MomCurrent RatingS0mA (DC)Voltage Rating - AC.Voltage Rating - DC24VActuator TypeRound, Button, FlushColor - Actuator/CapSilverIllumination Voltage (Nominal)24 VDCMounting TypePanel Mount, FrontIngress ProtectionScrew TerminalIngress ProtectionScrew TerminalFeaturesStailes SteelAnel Cutout DimensionsCircular J02 Mount		Pushbutton Switches
TypeVandal Resistant, IlluminatedTypeVandal Resistant, IlluminatedCircuitSPST-NOSwitch FunctionOff-MomCurrent RatingSomA (DC)Voltage Rating - AC-Voltage Rating - DC24VActuator TypeRound, Button, FlushColor - Actuator/CapSilverIllumination Voltage (Nominal)LED, GreenIllumination Voltage (Nominal)Srew TerminalIngress ProtectionSrew TerminalIngress ProtectionSilverFeaturesStailess SteelPanel Cutout DimensionsCircular - 19.20mm Dia	Package	-
CircuitSPST-NOSwitch FunctionOff-MomCurrent RatingS0mA (DC)Voltage Rating - AC-Voltage Rating - DC24VActuator TypeRound, Button, FlushColor - Actuator/CapSilverIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)Avent PontMounting TypeSorew TerminalIngress ProtectionSrew TerminalFeaturesStailess SteelPanel Cutout DimensionsCircular - 19.20mm Dia	Series	-
Switch FunctionOff-MomSwitch FunctionS0mA (DC)Current Rating - AC-Voltage Rating - AC24VActuator TypeRound, Button, FlushColor - Actuator/CapSilverIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)Arena Mount, FrontFermination StyleScrew TerminalIngress ProtectionIP66 - Dust Tight, Water ResistantFeaturesStainless SteelPanel Cutout DimensionsCircular - 19.20mm Dia	Туре	Vandal Resistant, Illuminated
Current Rating50mA (DC)Voltage Rating - AC-Voltage Rating - DC24VActuator TypeRound, Button, FlushColor - Actuator/CapSilverIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)24 VDCMounting TypeSinerIngress ProtectionSrew TerminalFeaturesStailess SteelPanel Mount DimensionsCircular - 19.20mm Dia	Circuit	SPST-NO
Voltage Rating - AC-Voltage Rating - DC24VActuator TypeRound, Button, FlushColor - Actuator/CapSilverIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)24 VDCMounting TypePanel Mount, FrontTermination StyleScrew TerminalIngress ProtectionIP66 - Dust Tight, Water ResistantFeaturesStainless SteelPanel Cutout DimensionsCircular - 19.20mm Dia	Switch Function	Off-Mom
Voltage Rating - DC24VActuator TypeRound, Button, FlushColor - Actuator/CapSilverIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)24 VDCMounting TypePanel Mount, FrontTermination StyleScrew TerminalIngress ProtectionIP66 - Dust Tight, Water ResistantFeaturesStainless SteelPanel Cutout DimensionsCircular - 19.20mm Dia	Current Rating	50mA (DC)
Actuator TypeRound, Button, FlushColor - Actuator/CapSilverIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)24 VDCMounting TypePanel Mount, FrontTermination StyleScrew TerminalIngress ProtectionIP66 - Dust Tight, Water ResistantFeaturesStainless SteelPanel Cutout DimensionsCircular - 19.20mm Dia	Voltage Rating - AC	-
Color - Actuator/CapSilverIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)24 VDCMounting TypePanel Mount, FrontTermination StyleScrew TerminalIngress ProtectionIP66 - Dust Tight, Water ResistantFeaturesStainless SteelPanel Cutout DimensionsCircular - 19.20mm Dia	Voltage Rating - DC	24V
Illumination Type, ColorLED, GreenIllumination Voltage (Nominal)24 VDCMounting TypePanel Mount, FrontTermination StyleScrew TerminalIngress ProtectionIP66 - Dust Tight, Water ResistantFeaturesStainless SteelPanel Cutout DimensionsCircular - 19.20mm Dia	Actuator Type	Round, Button, Flush
Illumination Voltage (Nominal)24 VDCMounting TypePanel Mount, FrontTermination StyleScrew TerminalIngress ProtectionIP66 - Dust Tight, Water ResistantFeaturesStainless SteelPanel Cutout DimensionsCircular - 19.20mm Dia	Color - Actuator/Cap	Silver
Mounting TypePanel Mount, FrontTermination StyleScrew TerminalIngress ProtectionIP66 - Dust Tight, Water ResistantFeaturesStainless SteelPanel Cutout DimensionsCircular - 19.20mm Dia	Illumination Type, Color	LED, Green
Termination StyleScrew TerminalIngress ProtectionIP66 - Dust Tight, Water ResistantFeaturesStainless SteelPanel Cutout DimensionsCircular - 19.20mm Dia	Illumination Voltage (Nominal)	24 VDC
Ingress ProtectionIP66 - Dust Tight, Water ResistantFeaturesStainless SteelPanel Cutout DimensionsCircular - 19.20mm Dia	Mounting Type	Panel Mount, Front
FeaturesStainless SteelPanel Cutout DimensionsCircular - 19.20mm Dia	Termination Style	Screw Terminal
Panel Cutout Dimensions Circular - 19.20mm Dia	Ingress Protection	IP66 - Dust Tight, Water Resistant
	Features	Stainless Steel
Report errors?	Panel Cutout Dimensions	Circular - 19.20mm Dia
1		Report errors?

MPI001/TE/GN/24 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MPI001/TE/GN/24 Payment Methods



MPI001/TE/GN/24 Shipping Methods



If you have any question about MPI001/TE/GN/24, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com