

# MR062C223KAA

### MR062C223KAA Information

Contact service stants there	 MR062C223KAA AVX Corporation Capacitors Ceramic Capacitors CAP CER 0.022UF 200V X7R RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# MR062C223KAA Specifications

ManufacturerAVX CorporationCapacitorsPackageCaranic CapacitorsPackageRadialSeriesCeralma ? MRCapacitance0.022 µFTolerance± 10%Voltage - Rated200 VTomperature Coefficient50°C ~ 125°CPactangs- 55°C ~ 125°CRatings- 61000000000000000000000000000000000000		
CapacitorsPackageRadialSeriesCeramic CapacitorsPackageRadialCapacitanceCeralan? MRCapacitance±10%Yoltage - Rated200VPoperature CoefficientX7ROperating Temperature-55°C ~ 125°CPatters-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.20°U x 0.00°U W (7.36mm x 2.28mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.20°U (5.08mm)Lead StyleStraight	Manufacturer Part Number	MR062C223KAA
Ceramic CapacitorsPackageRadialSeriesCeralam? MRCapacitance0.022µFTolerance±10%Voltage - Rated200VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSiz / Dimension0.290° L x 0.090° W (7.36mm x 2.28mm)Height - Seated (Max)-Thickness (Max)-Lead SpacingStraight	Manufacturer	AVX Corporation
PackageRadialSeriesCeralam? MRCapacitance0.022µFTolerance±10%Voltage - Rated200VTomperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeMough HoleSize / Dimension0.290° L x 0.090° W (7.36mm x 2.28mm)Height - Seated (Max)-Height - Seated (Max)-Height - Seated (Max)0.200° (5.08mm)Lead SpacingDavid (5.08mm)Lead StyleStraight	Category	Capacitors
Series   Ceralam? MR     Capacitance   0.022µF     Tolerance   ±10%     Voltage - Rated   200V     Tomperature Coefficient   X7R     Operating Temperature   -55°C ~ 125°C     Features   -     Ratings   -     Applications   General Purpose     Failure Rate   -     Mounting Type   Through Hole     Size / Dimension   0.290" L x 0.090" W (7.36mm x 2.28mm)     Height - Seated (Max)   -     Thickness (Max)   -     Lead Spacing   0.200" (5.08mm)     Lead Style   Straight		Ceramic Capacitors
Capacitance0.022µFTolerance±10%Voltage - Rated200VTemperature CoefficientXTROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HoleSize / Dimension0.290" L x 0.090" W (7.36mm x 2.28mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Package	Radial
Tolerance±10%Voltage - Rated200VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.290" L x 0.090" W (7.36mm x 2.28mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Series	Ceralam? MR
Voltage - Rated200VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.290" L x 0.090" W (7.36mm x 2.28mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Capacitance	0.022µF
Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.290" L x 0.090" W (7.36mm x 2.28mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.290" L x 0.090" W (7.36mm x 2.28mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Voltage - Rated	200V
Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.290" L x 0.090" W (7.36mm x 2.28mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Temperature Coefficient	X7R
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.290" L x 0.090" W (7.36mm x 2.28mm)Height - Seated (Max)0.290" (7.36mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.290" L x 0.090" W (7.36mm x 2.28mm)Height - Seated (Max)0.290" (7.36mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Features	-
Failure Rate-Failure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.290" L x 0.090" W (7.36mm x 2.28mm)Height - Seated (Max)0.290" (7.36mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Ratings	-
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.290" L x 0.090" W (7.36mm x 2.28mm)Height - Seated (Max)0.290" (7.36mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Applications	General Purpose
Package / CaseRadialSize / Dimension0.290" L x 0.090" W (7.36mm x 2.28mm)Height - Seated (Max)0.290" (7.36mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Failure Rate	-
Size / Dimension 0.290" L x 0.090" W (7.36mm x 2.28mm)   Height - Seated (Max) 0.290" (7.36mm)   Thickness (Max) -   Lead Spacing 0.200" (5.08mm)   Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max)0.290" (7.36mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Package / Case	Radial
Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleStraight	Size / Dimension	0.290" L x 0.090" W (7.36mm x 2.28mm)
Lead Spacing0.200" (5.08mm)Lead StyleStraight	Height - Seated (Max)	0.290" (7.36mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.200" (5.08mm)
Report errors?	Lead Style	Straight
		Report errors?

#### MR062C223KAA Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE ELARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### MR062C223KAA Payment Methods



## MR062C223KAA Shipping Methods



If you have any question about MR062C223KAA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com