



MS27484E12F35PD Information

Heisener.com

Part Number MS27484E12F35PD

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 22POS STRAIGHT W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27484E12F35PD Specifications

Manufacturer Part Number MS27484E12F35PD Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series Military, MIL-DTL-38999 Series II Connector Type Plug, Male Pins Number of Positions 22 Shell Size - Insert 12-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series II Connector Type Plug, Male Pins Number of Positions 22 Shell Size - Insert 12-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated Voltage - Rated Unrent Rating Series II Connectors, Interconnects Circular Connectors Circular Connectors Hull-DTL-38999 Series II Free Hanging II Series II Aluminum, Vickel Plated, Electroless Contact Finish Shell Material, Finish She	Manufacturer Part Number	MS27484E12F35PD
Package-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypePlug, Male PinsNumber of Positions22Shell Size - Insert12-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationDIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 500VDCCurrent Rating5A	Manufacturer	Amphenol Aerospace Operations
Package - Series Military, MIL-DTL-38999 Series II Connector Type Plug, Male Pins Number of Positions 22 Shell Size - Insert 12-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series II Connector Type Plug, Male Pins Number of Positions 22 Shell Size - Insert 12-35 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 55A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions22Shell Size - Insert12-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationDIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 500VDCCurrent Rating5A	Package	-
Number of Positions22Shell Size - Insert12-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationDIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 500VDCCurrent Rating5A	Series	Military, MIL-DTL-38999 Series II
Shell Size - Insert Shell Size, MIL	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating	Number of Positions	22
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Size - Insert	12-35
Termination Crimp Fastening Type Bayonet Lock Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Size, MIL	-
Fastening Type Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Mounting Type	Free Hanging (In-Line)
Orientation D Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Shell Material, Finish Aluminum, Nickel Plated, Electroless Gold Cold Shielded 400VAC, 500VDC 5A	Orientation	D
Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated 400VAC, 500VDC Current Rating 5A	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 400VAC, 500VDC Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	Shielded
	Voltage - Rated	400VAC, 500VDC
Report errors?	Current Rating	5A
		Report errors?

MS27484E12F35PD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27484E12F35PD Payment Methods





















MS27484E12F35PD Shipping Methods













If you have any question about MS27484E12F35PD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com