



MS27484T24F29P Information

Heisener.com

Part Number MS27484T24F29P

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 29POS STRAIGHT W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MS27484T24F29P Specifications

Manufacturer Part NumberMS27484T24F29PManufacturerAmphenol Aerospace OperationsCategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypePlug, Male PinsNumber of Positions29Shell Size - Insert24-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated600VAC, 850VDCCurrent Rating13A		
Category Connectors, Interconnects Circular Connectors Package - Series Military, MIL-DTL-38999 Series II Connector Type Plug, Male Pins Number of Positions 29 Shell Size - Insert 24-29 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Connectors, Interconnects Circular Connectors Hitterconnects Circular Connectors Allitary, MIL-DTL-38999 Series II Connectors II Nilitary, MIL-DTL-38999 Series II Nilitary, MIL-DTL-38999 Series II Flex II Nilitary, MIL-DTL-38999 Series II	Manufacturer Part Number	MS27484T24F29P
Circular Connectors Package - Series Military, MIL-DTL-38999 Series II Connector Type Plug, Male Pins Number of Positions 29 Shell Size - Insert 24-29 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Military, MIL-OTL-38999 Series II Military, MIL-DTL-38999 Series II Military, MIL-DTL-38999 Series II Military, MIL-DTL-38999 Series II Military, MIL-DTL-38999 Series II Alumical Pins Environment Spell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Voltage - Rated	Manufacturer	Amphenol Aerospace Operations
Package - Series Military, MIL-DTL-38999 Series II Connector Type Plug, Male Pins Number of Positions 29 Shell Size - Insert 24-29 Shell Size, MIL - Crimp Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series II Connector Type Plug, Male Pins Number of Positions 29 Shell Size - Insert 24-29 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC		Circular Connectors
Connector Type Plug, Male Pins Number of Positions 29 Shell Size - Insert 24-29 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated 600VAC, 850VDC	Package	-
Number of Positions Shell Size - Insert 24-29 Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated 29 24-29 Aluminum, Claretter Shell Material, Finish Gold Shielded 600VAC, 850VDC	Series	Military, MIL-DTL-38999 Series II
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 24-29 Crimp Free Hanging (In-Line) Free Hanging (In-Line) Crimp Bayonet Lock N (Normal) Environment Resistant Shell Material, Finish Gold Gold Footuact Finish Gold Shielded	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC	Number of Positions	29
Mounting Type Free Hanging (In-Line) Crimp Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Free Hanging (In-Line) Crimp Bayonet Lock N (Normal) Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Gold Footback Shielded 600VAC, 850VDC	Shell Size - Insert	24-29
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Ovoltage - Rated	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Aluminum, Nickel Plated, Electroless Gold 600VAC, 850VDC	Orientation	N (Normal)
Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated 600VAC, 850VDC	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 600VAC, 850VDC	Contact Finish	Gold
-	Features	Shielded
Current Rating 13A	Voltage - Rated	600VAC, 850VDC
	Current Rating	13A
Report errors?		Report errors?

MS27484T24F29P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MS27484T24F29P Payment Methods





















MS27484T24F29P Shipping Methods













If you have any question about MS27484T24F29P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com