



### MS27499E12B3SC Information

Heisener.com

Part Number MS27499E12B3SC

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 3POS BOX MNT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## MS27499E12B3SC Specifications

Manufacturer Part Number     MS27499E12B3SC       Manufacturer     Amphenol Aerospace Operations       Category     Connectors, Interconnects       Package     -       Series     Military, MIL-DTL-38999 Series II       Connector Type     Receptacle, Female Sockets       Number of Positions     3       Shell Size - Insert     12-3       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Crimp       Fastening Type     Bayonet Lock       Orientation     C       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Olive Drab Cadmium Plated       Contact Finish     Gold       Features     -       Voltage - Rated     900VAC, 1250VDC       Current Rating     13A   Report errors?		
Category Connectors, Interconnects Circular Connectors  Package - Series Military, MIL-DTL-38999 Series II Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 12-3 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Manufacturer Part Number	MS27499E12B3SC
Package-SeriesMilitary, MIL-DTL-38999 Series IIConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert12-3Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A	Manufacturer	Amphenol Aerospace Operations
Package - Series Military, MIL-DTL-38999 Series II  Connector Type Receptacle, Female Sockets  Number of Positions 3  Shell Size - Insert 12-3  Shell Size, MIL - Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock  Orientation C  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Gold  Features - Woltage - Rated 900VAC, 1250VDC  Current Rating 11	Category	Connectors, Interconnects
Series Military, MIL-DTL-38999 Series II  Connector Type Receptacle, Female Sockets  Number of Positions 3  Shell Size - Insert 12-3  Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert12-3Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A	Package	-
Number of Positions3Shell Size - Insert12-3Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A	Series	Military, MIL-DTL-38999 Series II
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated Outen Rating 13A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange  Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Number of Positions	3
Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock  Orientation C  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Gold  Features -  Voltage - Rated 900VAC, 1250VDC  Current Rating 13A	Shell Size - Insert	12-3
Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Shell Size, MIL	-
Fastening Type  Orientation  C  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  -  Voltage - Rated  900VAC, 1250VDC  Current Rating  13A	Mounting Type	Panel Mount, Flange
Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold Contact Finish Gold - 13A	Orientation	C
Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Contact Finish	Gold
Current Rating 13A	Features	-
	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	13A
		Report errors?

#### MS27499E12B3SC Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MS27499E12B3SC Payment Methods



















# MS27499E12B3SC Shipping Methods













If you have any question about MS27499E12B3SC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com