



### MS3102E28-10P Information

Heisener.com

**Part Number** MS3102E28-10P **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

**Description** CONN RCPT 7 POS BOX MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **MS3102E28-10P Specifications**

Manufacturer Part Number     MS3102E28-10P       Manufacturer     ITT Cannon, LLC       Category     Connectors, Interconnects       Package     -       Series     Military, MIL-DTL-5015, MS       Connector Type     Receptacle, Male Pins       Number of Positions     7       Shell Size - Insert     28-10       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Solder Cup       Fastening Type     Threaded       Orientation     N (Normal)       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum Alloy, Olive Drab Cadmium Plated       Contact Finish     Silver       Features     -       Voltage - Rated     500VAC, 700VDC       Current Rating     41A, 74A, 135A	Wiggiozitzo-tor Specifications	
Category Circular Connectors  Package - Series Military, MIL-DTL-5015, MS  Connector Type Receptacle, Male Pins  Number of Positions 7 Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated Current Rating 41A, 74A, 135A	Manufacturer Part Number	MS3102E28-10P
Package-SeriesMilitary, MIL-DTL-5015, MSConnector TypeReceptacle, Male PinsNumber of Positions7Shell Size - Insert28-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating41A, 74A, 135A	Manufacturer	ITT Cannon, LLC
Package - Military, MIL-DTL-5015, MS Connector Type Receptacle, Male Pins Number of Positions 7 Shell Size - Insert 28-10 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating 41A, 74A, 135A	Category	Connectors, Interconnects
Series Military, MIL-DTL-5015, MS  Connector Type Receptacle, Male Pins  Number of Positions 7  Shell Size - Insert 28-10  Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features  Voltage - Rated 500VAC, 700VDC  Current Rating 41A, 74A, 135A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions7Shell Size - Insert28-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating41A, 74A, 135A	Package	-
Number of Positions  Shell Size - Insert  28-10  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Voltage - Rated  500VAC, 700VDC  Current Rating  41A, 74A, 135A	Series	Military, MIL-DTL-5015, MS
Shell Size - Insert 28-10 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 41A, 74A, 135A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Features - Voltage - Rated 500VAC, 700VDC  Current Rating 41A, 74A, 135A	Number of Positions	7
Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features - Voltage - Rated 500VAC, 700VDC  Current Rating 41A, 74A, 135A	Shell Size - Insert	28-10
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 41A, 74A, 135A	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  -  Voltage - Rated  500VAC, 700VDC  Current Rating  Threaded  N (Normal)  Environment Resistant  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  -  41A, 74A, 135A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 41A, 74A, 135A	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 41A, 74A, 135A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  -  Voltage - Rated  500VAC, 700VDC  41A, 74A, 135A	Orientation	N (Normal)
Contact Finish Silver  Features - Voltage - Rated Current Rating 41A, 74A, 135A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 500VAC, 700VDC Current Rating 41A, 74A, 135A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 41A, 74A, 135A	Contact Finish	Silver
Current Rating 41A, 74A, 135A	Features	-
•	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	41A, 74A, 135A
The post of the last		Report errors?

### MS3102E28-10P Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MS3102E28-10P Payment Methods





















## MS3102E28-10P Shipping Methods













If you have any question about MS3102E28-10P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com