



## MS3470W12-8S Information

Heisener.com

Part Number MS3470W12-8S

Manufacturer TE Connectivity Deutsch Connectors

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 8POS FLANGE W/SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## MS3470W12-8S Specifications

Manufacturer Part Number       MS3470W12-8S         Manufacturer       TE Connectivity Deutsch Connectors         Category       Connectors, Interconnects         Package       -         Series       Military, MIL-DTL-26482 G Series II, AFD         Connector Type       Receptacle, Female Sockets         Number of Positions       8         Shell Size - Insert       12-8         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Olive Drab Cadmium Plated         Contact Finish       Gold         Features       -         Voltage - Rated       -         Current Rating       7.5A		
CategoryConnectors, InterconnectsPackage-SeriesMilitary, MIL-DTL-26482 G Series II, AFDConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A	Manufacturer Part Number	MS3470W12-8S
Package-SeriesMilitary, MIL-DTL-26482 G Series II, AFDConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A	Manufacturer	TE Connectivity Deutsch Connectors
Package-SeriesMilitary, MIL-DTL-26482 G Series II, AFDConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-26482 G Series II, AFDConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A	Package	-
Number of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A	Series	Military, MIL-DTL-26482 G Series II, AFD
Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Features - Voltage - Rated - Current Rating 7.5A	Number of Positions	8
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A	Shell Size - Insert	12-8
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated - Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated - Current Rating 7,5A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated - Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Gold  Features -  Voltage - Rated -  Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating 7.5A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated - Current Rating 7.5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated - Current Rating 7.5A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated - Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	-
	Voltage - Rated	-
Report errors?	Current Rating	7.5A
Report errors:		Report errors?

### MS3470W12-8S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# MS3470W12-8S Payment Methods


































If you have any question about MS3470W12-8S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com