

MY2-02-DC12 Information

Heisener.com

Part Number MY2-02-DC12

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MY2-02-DC12 Specifications

Manufacturer Part Number Mnufacturer Category Relays Power Relays, Over 2 Amps Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Peatures MY2-02-DC12 Omron Automation and Safety Relays Power Relays, Over 2 Amps AW Power Relays, Over 2 Amps Amps Pennst errors? Report errors?		
Category Relays Power Relays, Over 2 Amps Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Through Hole Termination Style PC Pin	Manufacturer Part Number	MY2-02-DC12
Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Through Hole Termination Style Purpose	Manufacturer	Omron Automation and Safety
Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Release Time 20ms Features - Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time20msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Series	MY
Coil Current Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Through Hole Termination Style 75mA 75mA 75mA 75mA 75mA 75mA 75mA 75mA	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Through Hole Termination Style	Coil Current	75mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Through Hole Termination Style	Coil Voltage	12VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 7 Turn Off Voltage (Min) 9.6 VDC 1.2 VDC Operate Time 20ms Release Time 20ms Features - Mounting Type Through Hole Termination Style 9.6 VDC 1.2 VDC Through Hole PC Pin	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features - Mounting Type Through Hole Termination Style 1.2 VDC 20ms Through Hole PC Pin	Switching Voltage	250VAC, 125VDC - Max
Operate Time 20ms Release Time 20ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	9.6 VDC
Release Time 20ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.2 VDC
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	20ms
Termination Style PC Pin	Features	-
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
Report circles.		Report errors?

MY2-02-DC12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MY2-02-DC12 Payment Methods





















MY2-02-DC12 Shipping Methods













If you have any question about MY2-02-DC12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com