

Heisener.com

MY4N-CR AC220/240 (S)

MY4N-CR AC220/240 (S) Information

Part Number MY4N-CR AC220/240 (S)
Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 3A 240V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MY4N-CR AC220/240 (S) Specifications

Manufacturer Part Number MY4N-CR AC220/240 (8) Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series MY Relay Type General Purpose Coil Type Non Latching Coil Current 4.2mA Coil Voltage 240VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.2mACoil Voltage240VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesLED Indicator, RC CircuitMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	MY4N-CR AC220/240 (S)
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.2mACoil Voltage240VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesLED Indicator, RC CircuitMounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package-SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.2mACoil Voltage240VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesLED Indicator, RC CircuitMounting TypeSocketableTermination StylePlug In	Category	Relays
SeriesMYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.2mACoil Voltage240VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesLED Indicator, RC CircuitMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 4.2mA Coil Voltage 240VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Release Time LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current4.2mACoil Voltage240VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesLED Indicator, RC CircuitMounting TypeSocketableTermination StylePlug In	Series	MY
Coil Current Coil Voltage 240VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage 240VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In	Coil Current	4.2mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In	Coil Voltage	240VAC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In	Contact Rating (Current)	3A
Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 20ms Release Time 20ms Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	192 VAC
Release Time 20ms Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	72 VAC
Features LED Indicator, RC Circuit Mounting Type Socketable Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	LED Indicator, RC Circuit
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

MY4N-CR AC220/240 (S) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MY4N-CR AC220/240 (S) Payment Methods



















MY4N-CR AC220/240 (S) Shipping Methods













If you have any question about MY4N-CR AC220/240 (S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com