



NJM5532DD Information

Heisener.com

For Reference Only

Part Number NJM5532DD

Manufacturer NJR Corporation/NJRC

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 10MHZ 8DIP **Package** 8-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NJM5532DD Specifications

Manufacturer Part NumberNJM5532DDManufacturerNJR Corporation/NJRCCategoryIntegrated Circuits (ICs)Linear - Amplifiers - Instrumentation, OP Amps, Buffer AmpsPackage8-DIP (0.300", 7.62mm)Series-Amplifier TypeGeneral PurposeNumber of Circuits2Output Type-Slew Rate8 V/μsGain Bandwidth Product10MHz-3db Bandwidth-Current - Input Bias200nAVoltage - Input Offset500μVCurrent - Supply9mACurrent - Output / Channel38mAVoltage - Supply, Single/Dual (±)±3 V ~ 20 VOperating Temperature-20°C ~ 75°CMounting TypeThrough HolePackage / Case8-DIP (0.300", 7.62mm)Supplier Device Package8-DIP	•	
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 8 V/μs Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 200nA Voltage - Input Offset 500μV Current - Supply 9mA Current - Output / Channel 38mA Voltage - Supply, Single/Dual (±) ±3 V ~ 20 V Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm)	Manufacturer Part Number	NJM5532DD
Linear - Amplifiers - Instrumentation, OP Amps, Buffer AmpsPackage8-DIP (0.300", 7.62mm)Series-Amplifier TypeGeneral PurposeNumber of Circuits2Output Type-Slew Rate8 V/μsGain Bandwidth Product10MHz-3db Bandwidth-Current - Input Bias200nAVoltage - Input Offset500μVCurrent - Supply9mACurrent - Output / Channel38mAVoltage - Supply, Single/Dual (±)±3 V ~ 20 VOperating Temperature-20°C ~ 75°CMounting TypeThrough HolePackage / Case8-DIP (0.300", 7.62mm)	Manufacturer	NJR Corporation/NJRC
Package 8-DIP (0.300", 7.62mm) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 8 V/μs Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 200nA Voltage - Input Offset 500μV Current - Supply 9mA Current - Output / Channel 38mA Voltage - Supply, Single/Dual (±) ±3 V ~ 20 V Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm)	Category	Integrated Circuits (ICs)
Series - General Purpose General Purpose Number of Circuits 2 - Output Type - Slew Rate 8 V/ μ s Gain Bandwidth Product 10MHz - 3db Bandwidth Product 10MHz - Input Bias 200nA - Current - Input Bias 200nA Voltage - Input Offset 500 μ V Current - Output / Channel 38mA		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier TypeGeneral PurposeNumber of Circuits2Output Type-Slew Rate8 V/μsGain Bandwidth Product10MHz-3db Bandwidth-Current - Input Bias200nAVoltage - Input Offset500μVCurrent - Supply9mACurrent - Output / Channel38mAVoltage - Supply, Single/Dual (±)±3 V ~ 20 VOperating Temperature-20°C ~ 75°CMounting TypeThrough HolePackage / Case8-DIP (0.300", 7.62mm)	Package	8-DIP (0.300", 7.62mm)
Number of Circuits 2 Output Type - Slew Rate 8 V/μs Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 200nA Voltage - Input Offset 500μV Current - Supply 9mA Current - Output / Channel 38mA Voltage - Supply, Single/Dual (±) ±3 V ~ 20 V Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm)	Series	-
Output Type - Slew Rate 8 V/μs Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 200nA Voltage - Input Offset 500μV Current - Supply 9mA Current - Output / Channel 38mA Voltage - Supply, Single/Dual (±) ±3 V ~ 20 V Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm)	Amplifier Type	General Purpose
Slew Rate $8 \text{ V/}\mu\text{s}$ Gain Bandwidth Product 10MHz -3db Bandwidth - Current - Input Bias 200nA Voltage - Input Offset $500 \mu\text{V}$ Current - Supply 9mA Current - Output / Channel 38mA Voltage - Supply, Single/Dual (±) $\pm 3 \text{ V} \sim 20 \text{ V}$ Operating Temperature $-20^{\circ}\text{C} \sim 75^{\circ}\text{C}$ Mounting Type $-20^{\circ}\text{C} \sim 75^{\circ}\text{C}$ Package / Case $-20^{\circ}\text{C} \sim 75^{\circ}\text{C}$	Number of Circuits	2
Gain Bandwidth Product -3db Bandwidth - Current - Input Bias 200nA Voltage - Input Offset 500μV Current - Supply 9mA Current - Output / Channel 38mA Voltage - Supply, Single/Dual (±) 43 V ~ 20 V Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm)	Output Type	-
$-3 db \ Bandwidth \\ -Current - Input \ Bias \\ 200 nA \\ Voltage - Input \ Offset \\ 500 \mu V \\ Current - Supply \\ 9mA \\ Current - Output / Channel \\ 38mA \\ Voltage - Supply, Single/Dual (\pm) \pm 3 \ V \sim 20 \ V Operating \ Temperature \\ -20^{\circ}C \sim 75^{\circ}C \\ Mounting \ Type \\ Through \ Hole \\ Package / Case \\ 8-DIP (0.300'', 7.62mm)$	Slew Rate	8 V/μs
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	Gain Bandwidth Product	10MHz
Voltage - Input Offset	-3db Bandwidth	-
Current - Supply9mACurrent - Output / Channel $38mA$ Voltage - Supply, Single/Dual (\pm) $\pm 3 \text{ V} \sim 20 \text{ V}$ Operating Temperature $-20^{\circ}\text{C} \sim 75^{\circ}\text{C}$ Mounting TypeThrough HolePackage / Case $8\text{-DIP }(0.300^{\circ}, 7.62mm)$	Current - Input Bias	200nA
Current - Output / Channel $38mA$ Voltage - Supply, Single/Dual (\pm) ± 3 V ~ 20 V Operating Temperature $-20^{\circ}\text{C} \sim 75^{\circ}\text{C}$ Mounting Type Through Hole Package / Case $8\text{-DIP } (0.300^{\circ}, 7.62mm)$	Voltage - Input Offset	500μV
Voltage - Supply, Single/Dual (\pm) ± 3 V ~ 20 V Operating Temperature -20° C ~ 75° C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm)	Current - Supply	9mA
Operating Temperature -20°C ~ 75°C Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm)	Current - Output / Channel	38mA
Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm)	Voltage - Supply, Single/Dual (±)	±3 V ~ 20 V
Package / Case 8-DIP (0.300", 7.62mm)	Operating Temperature	-20°C ~ 75°C
-	Mounting Type	Through Hole
Supplier Device Package 8-DIP	Package / Case	8-DIP (0.300", 7.62mm)
	Supplier Device Package	8-DIP
Report errors?		Report errors?

NJM5532DD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NJM5532DD Payment Methods



















NJM5532DD Shipping Methods













If you have any question about NJM5532DD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com