



NLP150L-96S5 Information



For Reference Only

Part Number NLP150L-96S5

Manufacturer Artesyn Embedded Technologies

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 5.1V 110W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NLP150L-96S5 Specifications

Manufacturer Part Number NLP150L-96SS Manufacturer Artesyn Embedded Technologies Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series NLP150L Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 22A Power (Watts) 110W (150W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 7.80" L x 3.80" W x 1.26" H (198.1mm x 96.5mm x 32.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series NLP150L Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 22A Power (Watts) 110W (150W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 7.80" L x 3.80" W x 1.26" H (198.1mm x 96.5mm x 32.0mm)	Manufacturer Part Number	NLP150L-96S5
Package - Series NLP150L Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 22A Power (Watts) 110W (150W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 7.80" L x 3.80" W x 1.26" H (198.1mm x 96.5mm x 32.0mm)	Manufacturer	Artesyn Embedded Technologies
Package - Series NLP150L Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 22A Power (Watts) 110W (150W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 7.80" L x 3.80" W x 1.26" H (198.1mm x 96.5mm x 32.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series NLP150L Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 22A Power (Watts) 110W (150W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 7.80" L x 3.80" W x 1.26" H (198.1mm x 96.5mm x 32.0mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 22A Power (Watts) 110W (150W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 7.80" L x 3.80" W x 1.26" H (198.1mm x 96.5mm x 32.0mm)	Package	-
Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 22A Power (Watts) 110W (150W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 7.80" L x 3.80" W x 1.26" H (198.1mm x 96.5mm x 32.0mm)	Series	NLP150L
Voltage - Input90 ~ 264 VACVoltage - Output 15.1VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)22APower (Watts)110W (150W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency73%Operating Temperature0°C ~ 70°C (With Derating)FeaturesLoad Sharing, Universal InputMounting TypeChassis MountSize / Dimension7.80" L x 3.80" W x 1.26" H (198.1mm x 96.5mm x 32.0mm)	Туре	Open Frame
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Size / Dimension 5.1V 6.1V 6	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation SkV (3000V) Efficiency Operating Temperature Features Load Sharing, Universal Input Mounting Type Chassis Mount 7.80" L x 3.80" W x 1.26" H (198.1mm x 96.5mm x 32.0mm)	Voltage - Output 1	5.1V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 7.80" L x 3.80" W x 1.26" H (198.1mm x 96.5mm x 32.0mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Sity (3000V) Efficiency 73% Operating Temperature O°C ~ 70°C (With Derating) Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 22A 110W (150W Forced Air) ITE (Commercial) Sity (3000V) Commercial) Abv (3000V) Commercial) Available (Commercial) Ava	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 7.80" L x 3.80" W x 1.26" H (198.1mm x 96.5mm x 32.0mm)	Voltage - Output 4	-
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Current - Output (Max)	22A
Voltage - Isolation 3kV (3000V) Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 7.80" L x 3.80" W x 1.26" H (198.1mm x 96.5mm x 32.0mm)	Power (Watts)	110W (150W Forced Air)
Efficiency 73% Operating Temperature 0°C ~ 70°C (With Derating) Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 7.80" L x 3.80" W x 1.26" H (198.1mm x 96.5mm x 32.0mm)	Applications	ITE (Commercial)
Operating Temperature 0°C ~ 70°C (With Derating) Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 7.80" L x 3.80" W x 1.26" H (198.1mm x 96.5mm x 32.0mm)	Voltage - Isolation	3kV (3000V)
Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 7.80" L x 3.80" W x 1.26" H (198.1mm x 96.5mm x 32.0mm)	Efficiency	73%
Mounting Type Chassis Mount Size / Dimension 7.80" L x 3.80" W x 1.26" H (198.1mm x 96.5mm x 32.0mm)	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Size / Dimension 7.80" L x 3.80" W x 1.26" H (198.1mm x 96.5mm x 32.0mm)	Features	Load Sharing, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	7.80" L x 3.80" W x 1.26" H (198.1mm x 96.5mm x 32.0mm)
		Report errors?

NLP150L-96S5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NLP150L-96S5 Payment Methods



















NLP150L-96S5 Shipping Methods













If you have any question about NLP150L-96S5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com