

NPPC341KFXD-RC

NPPC341KFXD-RC Information

Heisener.com

For Reference Only

Part Number NPPC341KFXD-RC

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description CONN HEADER .100" 34POS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









NPPC341KFXD-RC Specifications

Manufacturer Part Number NPPC341KFXD-RC Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Connector Type Header, Top or Bottom Entry Contact Type Female Socket Style Board to Board Number of Positions 34 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color - Insulation Height 0.279" (7.10mm)		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series - Connector Type Header, Top or Bottom Entry Contact Type Female Socket Style Board to Board Number of Positions 34 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Surface Mount Termination Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color - Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Rectangular Connectors - Headers, Receptacles, Female Sockets Rectangular Connectors - Headers, Receptacles, Female Sockets Rectangular Connectors - Headers, Receptacles, Female Sockets Rectangular Connectors - Headers, Receptacles, Female Sockets Rectangular Connectors - Headers, Receptacles, Female Sockets Sockets	Manufacturer Part Number	NPPC341KFXD-RC
Package-Series-Connector TypeHeader, Top or Bottom EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions34Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation Color-	Manufacturer	Sullins Connector Solutions
Package - Series - Connector Type Header, Top or Bottom Entry Contact Type Female Socket Style Board to Board Number of Positions 34 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color -	Category	Connectors, Interconnects
Series - Connector Type Header, Top or Bottom Entry Contact Type Female Socket Style Board to Board Number of Positions 34 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color -		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Header, Top or Bottom Entry Contact Type Female Socket Style Board to Board Number of Positions 34 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color -	Package	-
Contact Type Female Socket Style Board to Board Number of Positions 34 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color -	Series	-
Style Board to Board Number of Positions 34 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color -	Connector Type	Header, Top or Bottom Entry
Number of Positions Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating Mounting Type Surface Mount Termination Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color -	Contact Type	Female Socket
Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color -	Style	Board to Board
Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color -	Number of Positions	34
Number of Rows1Row Spacing - Mating-Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation Color-	Number of Positions Loaded	All
Row Spacing - Mating Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color -	Pitch - Mating	0.100" (2.54mm)
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation Color-	Number of Rows	1
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color -	Row Spacing - Mating	-
Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color -	Mounting Type	Surface Mount
Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color -	Termination	Solder
Contact Finish Thickness - Mating Flash Insulation Color -	Fastening Type	Push-Pull
Insulation Color -	Contact Finish - Mating	Gold
	Contact Finish Thickness - Mating	Flash
Insulation Height 0.279" (7.10mm)	Insulation Color	-
	Insulation Height	0.279" (7.10mm)
Contact Length - Post -	Contact Length - Post	-
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Operating Temperature	-40°C ~ 105°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Gold
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

NPPC341KFXD-RC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

NPPC341KFXD-RC Payment Methods



















NPPC341KFXD-RC Shipping Methods













If you have any question about NPPC341KFXD-RC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com