

OMI-SS-205L,500 Information

Heisener.com

Part Number OMI-SS-205L,500

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

Description RELAY GENERAL PURPOSE DPDT 5A 5V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









OMI-SS-205L,500 Specifications

Manufacturer OMI-SS-205L,500 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series OMI, OEG Relay Type General Purpose Coil Type Non Latching Coil Current 108mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.25 VDC Operate Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesOMI, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current108mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.25 VDCOperate Time20msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	OMI-SS-205L,500
Package - Series OMI, OEG Relay Type General Purpose Coil Type Non Latching Coil Current 108mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.25 VDC Operate Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesOMI, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current108mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.25 VDCOperate Time20msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesOMI, OEGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current108mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.25 VDCOperate Time20msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current108mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.25 VDCOperate Time20msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current108mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.25 VDCOperate Time20msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Series	OMI, OEG
Coil Current108mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.25 VDCOperate Time20msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.25 VDC Operate Time 20ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 7urn Off Voltage (Min) 0.25 VDC Operate Time 20ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Current	108mA
Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.25 VDC Operate Time 20ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	5VDC
Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.25 VDC Operate Time 20ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 20ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style 3.75 VDC 3.75 VDC Sealed - Flux Protection	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 20ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC, 30VDC - Max
Operate Time 20ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	3.75 VDC
Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.25 VDC
Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	8ms
Termination Style PC Pin	Features	Sealed - Flux Protection
	Mounting Type	Through Hole
Papart arrors?	Termination Style	PC Pin
Report errors:		Report errors?

OMI-SS-205L,500 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

OMI-SS-205L,500 Payment Methods



















OMI-SS-205L,500 Shipping Methods













If you have any question about OMI-SS-205L,500, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com