



Heisener.com

### P61-100-A-A-I12-20MA-C Information

Part Number P61-100-A-A-I12-20MA-C

Manufacturer SSI Technologies Inc Category Sensors, Transducers

Pressure Sensors, Transducers

**Description** SENSOR 100PSIA 1/4 NPT W/TEMP

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## P61-100-A-A-I12-20MA-C Specifications

Manufacturer Part Number       P61-100-A-A-I12-20MA-C         Manufacturer       SSI Technologies Inc         Category       Sensors, Transducers         Package       Cylinder         Series       MediaSensor?         Pressure Type       Absolute         Operating Pressure       100 PSI (689.48 kPa)         Output Type       Analog Current         Output       4 mA ~ 20 mA         Accuracy       ±0.5%         Voltage - Supply       8 V ~ 30 V         Port Size       Male - 1/4" (6.35mm) NPT         Port Style       Threaded         Features       -         Termination Style       12" Integral Harness         Maximum Pressure       300 PSI (2068.43 kPa)         Operating Temperature       -40°C ~ 105°C         Package / Case       Cylinder         Supplier Device Package       -		
Category         Sensors, Transducers           Package         Cylinder           Series         MediaSensor?           Pressure Type         Absolute           Operating Pressure         100 PSI (689.48 kPa)           Output Type         Analog Current           Output         4 mA ~ 20 mA           Accuracy         ±0.5%           Voltage - Supply         8 V ~ 30 V           Port Size         Male - 1/4" (6.35mm) NPT           Port Style         Threaded           Features         -           Termination Style         12" Integral Harness           Maximum Pressure         300 PSI (2068.43 kPa)           Operating Temperature         -40°C ~ 105°C           Package / Case         Cylinder           Supplier Device Package         -	Manufacturer Part Number	P61-100-A-A-I12-20MA-C
Package Cylinder Series MediaSensor? Pressure Type Absolute Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.5% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features - Termination Style 12" Integral Harness Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -40°C ~ 105°C Package / Case Cylinder Supplier Device Package	Manufacturer	SSI Technologies Inc
Package         Cylinder           Series         MediaSensor?           Pressure Type         Absolute           Operating Pressure         100 PSI (689.48 kPa)           Output Type         Analog Current           Output         4 mA ~ 20 mA           Accuracy         ±0.5%           Voltage - Supply         8 V ~ 30 V           Port Size         Male - 1/4" (6.35mm) NPT           Port Style         Threaded           Features         -           Termination Style         12" Integral Harness           Maximum Pressure         300 PSI (2068.43 kPa)           Operating Temperature         -40°C ~ 105°C           Package / Case         Cylinder           Supplier Device Package         -	Category	Sensors, Transducers
SeriesMediaSensor?Pressure TypeAbsoluteOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style12" Integral HarnessMaximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeAbsoluteOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style12" Integral HarnessMaximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Package	Cylinder
Operating Pressure  Output Type  Analog Current  Output  4 mA ~ 20 mA  Accuracy  by Voltage - Supply  Port Size  Male - 1/4" (6.35mm) NPT  Port Style  Threaded  Features  -  Termination Style  12" Integral Harness  Maximum Pressure  300 PSI (2068.43 kPa)  Operating Temperature  -40°C ~ 105°C  Package / Case  Supplier Device Package  -  100 PSI (689.48 kPa)  Analog Current  4 mA ~ 20 mA  + 40.5%  Threaded  12" Integral Harness  Cylinder  -40°C ~ 105°C  Cylinder	Series	MediaSensor?
Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.5%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeatures-Termination Style12" Integral HarnessMaximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Pressure Type	Absolute
Output 4 mA ~ 20 mA  Accuracy ±0.5%  Voltage - Supply 8 V ~ 30 V  Port Size Male - 1/4" (6.35mm) NPT  Port Style Threaded  Features -  Termination Style 12" Integral Harness  Maximum Pressure 300 PSI (2068.43 kPa)  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Operating Pressure	100 PSI (689.48 kPa)
Accuracy ±0.5%  Voltage - Supply 8 V ~ 30 V  Port Size Male - 1/4" (6.35mm) NPT  Port Style Threaded  Features -  Termination Style 12" Integral Harness  Maximum Pressure 300 PSI (2068.43 kPa)  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Output Type	Analog Current
Voltage - Supply  Port Size  Male - 1/4" (6.35mm) NPT  Port Style  Threaded  Features  -  Termination Style  12" Integral Harness  Maximum Pressure  300 PSI (2068.43 kPa)  Operating Temperature  -40°C ~ 105°C  Package / Case  Cylinder  Supplier Device Package	Output	4 mA ~ 20 mA
Port Size Male - 1/4" (6.35mm) NPT  Port Style Threaded  Features -  Termination Style 12" Integral Harness  Maximum Pressure 300 PSI (2068.43 kPa)  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Accuracy	±0.5%
Port Style Threaded  Features -  Termination Style 12" Integral Harness  Maximum Pressure 300 PSI (2068.43 kPa)  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Voltage - Supply	8 V ~ 30 V
Features - Termination Style 12" Integral Harness  Maximum Pressure 300 PSI (2068.43 kPa)  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Port Size	Male - 1/4" (6.35mm) NPT
Termination Style 12" Integral Harness  Maximum Pressure 300 PSI (2068.43 kPa)  Operating Temperature -40°C ~ 105°C  Package / Case Cylinder  Supplier Device Package -	Port Style	Threaded
Maximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Features	-
Operating Temperature-40°C ~ 105°CPackage / CaseCylinderSupplier Device Package-	Termination Style	12" Integral Harness
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	300 PSI (2068.43 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 105°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
Report crists:		Report errors?

#### P61-100-A-A-I12-20MA-C Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### P61-100-A-A-I12-20MA-C Payment Methods



















# P61-100-A-A-I12-20MA-C Shipping Methods













If you have any question about P61-100-A-A-I12-20MA-C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com