

**PBC33DFDN Information**


For Reference Only

**Part Number** [PBC33DFDN](#)  
**Manufacturer** Sullins Connector Solutions  
**Category** Connectors, Interconnects  
[Rectangular Connectors - Headers, Male Pins](#)  
**Description** CONN HEADER .100 DUAL STR 66POS  
**Package** -  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)



[Request a Quote](#)

**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**PBC33DFDN Specifications**

|                            |  |
|----------------------------|--|
| Manufacturer Part Number   | <a href="#">PBC33DFDN</a>  |
| Manufacturer               | Sullins Connector Solutions  |
| Category                   | Connectors, Interconnects<br><a href="#">Rectangular Connectors - Headers, Male Pins</a> |
| Package                    | -  |
| Series                     | -  |
| Connector Type             | Header, Breakaway  |
| Contact Type               | Male Pin   |
| Pitch - Mating             | 0.100" (2.54mm)  |
| Style                      | Board to Board or Cable  |
| Shrouding                  | Unshrouded   |
| Number of Positions        | 66   |
| Number of Positions Loaded | All  |
| Number of Rows             | 2  |
| Row Spacing - Mating       | 0.100" (2.54mm)  |
| Mounting Type              | Through Hole   |
| Termination                | Solder   |
| Fastening Type             | Push-Pull  |
| Contact Length - Mating    | 0.318" (8.08mm)  |
| Contact Length - Post      | 0.420" (10.67mm)   |
| Overall Contact Length     | 0.838" (21.29mm)   |
| Insulation Height          | 0.100" (2.54mm)  |
| Contact Shape              | Square   |
| Contact Finish - Mating    | Gold   |

|                                   |                                  |
|-----------------------------------|----------------------------------|
| Contact Finish Thickness - Mating | 10µin (0.25µm)                   |
| Contact Finish - Post             | Tin                              |
| Contact Material                  | Phosphor Bronze                  |
| Insulation Material               | Polybutylene Terephthalate (PBT) |
| Features                          | -                                |
| Operating Temperature             | -65°C ~ 125°C                    |
| Ingress Protection                | -                                |
| Material Flammability Rating      | UL94 V-0                         |
| Insulation Color                  | Black                            |
|                                   | <a href="#">Report errors?</a>   |

## PBC33DFDN Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## PBC33DFDN Payment Methods



## PBC33DFDN Shipping Methods



If you have any question about PBC33DFDN, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)