

PBRC-5.06BR

PBRC-5.06BR Information

- 28
Re



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PBRC-5.06BR Specifications

ManufacturerAVX Corp/Kyocera CorpCategoryCrystals, Oscillators, ResonatorsResonatorsPackage3-SMD, Non-StandardSeriesPBRC-B, KyoceraTypeCeramicType5.06MHzFrequency Stability±0.3%Frequency Tolerance±0.5%FaturesBuilt in CapacitorCapacitance33pFImpedance20°C ~ 80°CMounting TypeSurface MountPackage / Case3-SMD, Non-StandardSize / Dimension0.291" L x 0.134" W (7.40mm x 3.40mm)		
CategoryCrystals, Oscillators, ResonatorsResonatorsPackage3-SMD, Non-StandardSeriesPBRC-B, KyoceraTypeCeramicFrequency5.06MHzFrequency Stability±0.3%Frequency Tolerance±0.5%FaturesBuilt in CapacitorCapacitance33pFImpedance20°C ~ 80°CMounting TypeSurface MountPackage / Case3-SMD, Non-StandardSize / Dimension0.991" (L x 0.134" W (7.40mm x 3.40mm)Height0.091" (2.30mm)	Manufacturer Part Number	PBRC-5.06BR
ResonatorsPackage3-SMD, Non-StandardSeriesPBRC-B, KyoceraTypeCeramicFrequency5.06MHzFrequency Stability±0.3%Frequency Tolerance±0.5%Built in CapacitorCapacitance33pFImpedance30 OhmOperating Temperature-20°C ~ 80°CMounting TypeSurface MountPackage / Case3-SMD, Non-StandardSize / Dimension0.291" L x 0.134" W (7.40mm x 3.40mm)Height0.091" (2.30mm)	Manufacturer	AVX Corp/Kyocera Corp
Package3-SMD, Non-StandardSeriesPBRC-B, KyoceraTypeCeramicType5.06MHzFrequency Stability±0.3%Frequency Tolerance±0.5%FeaturesBuilt in CapacitorCapacitance33pFImpedance00hmOperating TemperatureSurface MountPackage / CaseSurface MountSize / Dimension0.291" L x 0.134" W (7.40mm x 3.40mm)Height0.091" (2.30mm)	Category	Crystals, Oscillators, Resonators
SeriesPBRC-B, KyoceraTypeCeramicFrequency5.06MHzFrequency Stability±0.3%Frequency Tolerance±0.5%FeaturesBuilt in CapacitorCapacitance33pFImpedance30 OhmOperating Temperature-20°C ~ 80°CMounting TypeSurface MountPackage / Case3.SMD, Non-StandardSize / Dimension0.291" L x 0.134" W (7.40mm x 3.40mm)Height0.091" (2.30mm)		Resonators
TypeCeramicFrequency5.06MHzFrequency Stability±0.3%Frequency Tolerance±0.5%FeaturesBuilt in CapacitorCapacitance33pFImpedance30 OhmOperating Temperature-20°C ~ 80°CMounting TypeSurface MountPackage / Case3-SMD, Non-StandardSize / Dimension0.291" L x 0.134" W (7.40mm x 3.40mm)Height0.091" (2.30mm)	Package	3-SMD, Non-Standard
Frequency5.06MHzFrequency Stability±0.3%Frequency Tolerance±0.5%FeaturesBuilt in CapacitorCapacitance33pFImpedance30 OhmOperating Temperature-20°C ~ 80°CMounting TypeSurface MountPackage / Case3-SMD, Non-StandardSize / Dimension0.291" L x 0.134" W (7.40mm x 3.40mm)Height0.091" (2.30mm)	Series	PBRC-B, Kyocera
Frequency Stability±0.3%Frequency Tolerance±0.5%FeaturesBuilt in CapacitorCapacitance33pFImpedance30 OhmOperating Temperature-20°C ~ 80°CMounting TypeSurface MountPackage / Case3-SMD, Non-StandardSize / Dimension0.291" L x 0.134" W (7.40mm x 3.40mm)Height0.091" (2.30mm)	Туре	Ceramic
Frequency Tolerance±0.5%FeaturesBuilt in CapacitorCapacitance33pFImpedance30 OhmOperating Temperature-20°C ~ 80°CMounting TypeSurface MountPackage / Case3-SMD, Non-StandardSize / Dimension0.291" L x 0.134" W (7.40mm x 3.40mm)Height0.091" (2.30mm)	Frequency	5.06MHz
FeaturesBuilt in CapacitorCapacitance33pFImpedance30 OhmOperating Temperature-20°C ~ 80°CMounting TypeSurface MountPackage / Case3-SMD, Non-StandardSize / Dimension0.291" L x 0.134" W (7.40mm x 3.40mm)Height0.091" (2.30mm)	Frequency Stability	±0.3%
Capacitance33pFImpedance30 OhmOperating Temperature-20°C ~ 80°CMounting TypeSurface MountPackage / Case3-SMD, Non-StandardSize / Dimension0.291" L x 0.134" W (7.40mm x 3.40mm)Height0.091" (2.30mm)	Frequency Tolerance	$\pm 0.5\%$
Impedance30 OhmOperating Temperature-20°C ~ 80°CMounting TypeSurface MountPackage / Case3-SMD, Non-StandardSize / Dimension0.291" L x 0.134" W (7.40mm x 3.40mm)Height0.091" (2.30mm)	Features	Built in Capacitor
Operating Temperature-20°C ~ 80°CMounting TypeSurface MountPackage / Case3-SMD, Non-StandardSize / Dimension0.291" L x 0.134" W (7.40mm x 3.40mm)Height0.091" (2.30mm)	Capacitance	33pF
Mounting TypeSurface MountPackage / Case3-SMD, Non-StandardSize / Dimension0.291" L x 0.134" W (7.40mm x 3.40mm)Height0.091" (2.30mm)	Impedance	30 Ohm
Package / Case 3-SMD, Non-Standard Size / Dimension 0.291" L x 0.134" W (7.40mm x 3.40mm) Height 0.091" (2.30mm)	Operating Temperature	-20°C ~ 80°C
Size / Dimension 0.291" L x 0.134" W (7.40mm x 3.40mm) Height 0.091" (2.30mm)	Mounting Type	Surface Mount
Height 0.091" (2.30mm)	Package / Case	3-SMD, Non-Standard
•	Size / Dimension	0.291" L x 0.134" W (7.40mm x 3.40mm)
Report errors?	Height	0.091" (2.30mm)
		Report errors?

PBRC-5.06BR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

PBRC-5.06BR Payment Methods



PBRC-5.06BR Shipping Methods



If you have any question about PBRC-5.06BR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com