

PCM-400-18-U

uote

PCM-400-18-U Information

	Part Number Manufacturer Category Description Package	PCM-400-18-U CUI Inc. Power Supplies - External/Internal (Off-Board) AC DC Converters AC/DC CONVERTER 18V 220W - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Qu

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PCM-400-18-U Specifications

ManufacturerCUI Inc.CategoryPower Supplies - External/Internal (Off-Board)Ac DC ConvertersPackage-SeriesPCM-400StriesOpen FrameNumber of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 10 ~ 264 VACVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Solation-Voltage - Solation- <th></th> <th></th> <th></th>			
CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesPCM-400TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 118VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4202W (400W Forced Air)Current - Output (Max)1E (Commercial)Voltage - Isolation3KV (3000V)Efficiency85%Operating TemperatureOrc ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Remote On/Off, Standby Output, Universal InputMounting Type6.00° L x 4.00° W x 1.50° H (152.4mm x 101.6mm x 38.1mm)	Manufacturer Part Number		
AC DC Converters Package - Series PCM-400 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 18V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Soutput 4 - Voltage - Soutput 5 220W (400W Forced Air) Power (Watts) 220W (400W Forced Air) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00° L x 4.00° W x 1.50° H (152.4mm x 101.6mm x 38.1mm)	Manufacturer		
Package-SeriesPCM-400TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 118VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 412.2APower (Watts)20W (400W Forced Air)Voltage - Isolation1FL (Commercial)Voltage - IsolationS%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustabe Output, PEC, Remote On/Off, Standby Output, Universal InputMounting Type6.00° L x 4.00° W x 1.50° H (152.4mm x 101.6mm x 38.1mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series PCM-400 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 18V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.22A Power (Watts) 20W (400W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature Adjustable Output, PFC, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)		AC DC Converters	
TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 118VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 42020 (400W Forced Air)Power (Wats)122 (2000 W Forced Air)Applications17E (Commercial)Voltage - Isolation3kV (3000V)Efficiency65%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Remote On/Off, Standby Output, Universal InputMounting Type6.00° L x 4.00° W x 1.50° H (152.4mm x 101.6mm x 38.1mm)	Package	-	
Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 18V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 4 - Current - Output (Max) 12.22A Power (Watts) 220W (400W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Series	PCM-400	
Voltage - Input 90 ~ 264 VAC Voltage - Output 1 18V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 4 - Current - Output (Max) 12.22A Power (Watts) 200W (400W Forced Air) Applications TE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote On/Off, Standby Output, Universal Input Mounting Type 6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Туре	Open Frame	
Voltage - Output 1 18V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.22A Power (Watts) 220W (400W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote On/Off, Standby Output, Universal Input Mounting Type 6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Number of Outputs	1	
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12.22A Power (Watts) 220W (400W Forced Air) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 85% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Remote On/Off, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Voltage - Input	90 ~ 264 VAC	
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)12.22APower (Watts)220W (400W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency85%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Remote On/Off, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Voltage - Output 1	18V	
Voltage - Output 4-Current - Output (Max)12.22APower (Watts)220W (400W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency85%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Remote On/Off, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Voltage - Output 2	-	
Current - Output (Max)12.22APower (Watts)220W (400W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency85%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Remote On/Off, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Voltage - Output 3	-	
Power (Watts)220W (400W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency85%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Remote On/Off, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Voltage - Output 4	-	
ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency85%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Remote On/Off, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Current - Output (Max)	12.22A	
Voltage - Isolation3kV (3000V)Efficiency85%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Remote On/Off, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Power (Watts)	220W (400W Forced Air)	
Efficiency85%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Remote On/Off, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Applications	ITE (Commercial)	
Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Remote On/Off, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Voltage - Isolation	3kV (3000V)	
FeaturesAdjustable Output, PFC, Remote On/Off, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Efficiency	85%	
Mounting TypeChassis MountSize / Dimension6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Operating Temperature	0° C ~ 70° C (With Derating)	
Size / Dimension 6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	Features	Adjustable Output, PFC, Remote On/Off, Standby Output, Universal Input	
	Mounting Type	Chassis Mount	
Report errors	Size / Dimension	6.00" L x 4.00" W x 1.50" H (152.4mm x 101.6mm x 38.1mm)	
			Report errors?

PCM-400-18-U Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

PCM-400-18-U Payment Methods



PCM-400-18-U Shipping Methods



If you have any question about PCM-400-18-U, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com