

PE014024 Information



For Reference Only

Part Number PE014024

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 5A 24V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PE014024 Specifications

Manufacturer Part NumberPE014024ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesPE, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.8mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time8msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesPE, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.8mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time8msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	PE014024
Package-SeriesPE, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.8mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time8msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesPE, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.8mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time8msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesPE, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.8mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time8msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.8mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time8msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current 8.8mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 400VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Series	PE, SCHRACK
Coil Current8.8mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time8msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 400VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 8ms Release Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 400VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 8ms Release Time 8ms Release Time Sealed - Flux Protection Mounting Type Through Hole Termination Style	Coil Current	8.8mA
Contact Rating (Current) Switching Voltage 400VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	24VDC
Switching Voltage 400VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	5A
Turn Off Voltage (Min) 2.4 VDC Operate Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	400VAC - Max
Operate Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	18 VDC
Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	2.4 VDC
Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	8ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	8ms
Termination Style PC Pin	Features	Sealed - Flux Protection
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

PE014024 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PE014024 Payment Methods





















PE014024 Shipping Methods













If you have any question about PE014024, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com