

PIC18F4423-I/ML

PIC18F4423-I/ML Information

WWW.deatericites.m File File File File File File Duunuut	PIC18F4423-I/ML Microchip Technology Integrated Circuits (ICs) Embedded - Microcontrollers IC MCU 8BIT 16KB FLASH 44QFN 44-VQFN Exposed Pad For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PIC18F4423-I/ML Specifications

Interfactor Microchi Technology Ianufacturer Microchi Technology Integrated Circuits (ICs) Embedded - Microcontrollers ackage 44-VQFN Exposed Pad ackage PIC? 18F ore Processor PIC ore Processor PIC ore Size 8-Bit onectivity 12C, SPI, UART/USART onnectivity Sown-out Detect/Reset, HLVD, POR, PWM, WDT orgram Memory Size 16KB (8K x 16) rogram Memory Size 16KB (8K x 16) rogram Memory Type FLASH EPROM Size 256 x 8 Ad Size 768 x 8 oltage - Supply (Vcc/Vdd) 4.2 V ~ 5.5 V ata Converters A/D 13x12b scillator Type Internal perating Temperature 40°C ~ 85°C (TA) ackage / Case 44-VQFN Exposed Pad		
ategoryIntegrated Circuits (ICs)Embedded - Microcontrollersackage44-VQFN Exposed PaderiesPIC? 18Fore ProcessorPICore Size8-Bitpeed40MHzonnectivityI2C, SPI, UART/USARTeripheralsBrown-out Detect/Reset, HLVD, POR, PWM, WDTumber of I/O36rogram Memory Size16KB (8K x 16)EPROM Size256 x 8AM Size768 x 8olage - Supply (Vcc/Vdd)4.2 V ~ 5.5 Vata ConvertersA/D 13x12bscillator TypeInternaluperating Temperature-40°C ~ 85°C (TA)touting Type-ackage / Case44-VQFN Exposed Pad	Manufacturer Part Number	PIC18F4423-I/ML
Embedded - Microcontrollers ackage 44-VQFN Exposed Pad perfers PIC? 18F ore Processor PIC ore Size 8-Bit peed 40MHz onnectivity I2C, SPI, UART/USART peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT orgram Memory Size 16KB (8K x 16) rogram Memory Type FLASH EPROM Size 256 x 8 AM Size 768 x 8 olage - Supply (Vcc/Vdd) 4.2 V ~ 5.5 V ata Converters A/D 13x12b scillator Type Internal upperating Temperature -40°C ~ 85°C (TA) ackage / Case 44-VQFN Exposed Pad	Manufacturer	Microchip Technology
ackage 44-VQFN Exposed Pad eries PIC? 18F ore Processor PIC ore Processor 8-Bit ore Size 8-Bit peed 40MHz onnectivity I2C, SPI, UART/USART ore processor Brown-out Detect/Reset, HLVD, POR, PWM, WDT oruber of I/O 36 orogram Memory Size I6KB (8K x 16) rogram Memory Type FLASH EPROM Size 256 x 8 AM Size 768 x 8 oltage - Supply (Vcc/Vdd) 4.2 V ~ 5.5 V scillator Type Internal upertaing Temperature -40°C ~ 85°C (TA) outning Type 44-VQFN Exposed Pad	Category	Integrated Circuits (ICs)
erriesPIC? 18Fore ProcessorPICore Size8-Bitpeed40MHzonnectivityI2C, SPI, UART/USARTeripheralsBrown-out Detect/Reset, HLVD, POR, PWM, WDTumber of I/O36rogram Memory Size16KB (8K x 16)rogram Memory TypeFLASHEPROM Size256 x 8oltage - Supply (Vcc/Vdd)4.2 V ~ 5.5 Vata ConvertersA/D 13x12bscillator TypeInternaluperating Temperature-40°C ~ 85°C (TA)ackage / Case44-VQFN Exposed Pad		Embedded - Microcontrollers
ore ProcessorPICore Size8-Bitpeed40MHzonnectivityI2C, SPI, UART/USARTonnectivityBrown-out Detect/Reset, HLVD, POR, PWM, WDToumber of J/O36orgram Memory SizeI6KB (8K x 16)rogram Memory Type256 x 8AM Size768 x 8oltage - Supply (Vcc/Vdd)4.2 V ~ 5.5 Vtata ConvertersInternalscillator TypeInternaluperating Temperature4.0°C ~ 85°C (TA)tatage / Case44-VQFN Exposed Pad	Package	44-VQFN Exposed Pad
ore Size8-Bitpeed40MHzonnectivity12C, SPI, UART/USARTeripheralsBrown-out Detect/Reset, HLVD, POR, PWM, WDTounder of I/O36orogram Memory Size16KB (8K x 16)rogram Memory Type526 x 8AM Size768 x 8oltage - Supply (Vcc/Vdd)4.2 V ~ 5.5 VvacorverersInternaluperating Temperature4.0°C ~ 85°C (TA)outning Type44-VQFN Exposed Pad	Series	PIC? 18F
peed40MHzonnectivityI2C, SPI, UART/USARTeripheralsBrown-out Detect/Reset, HLVD, POR, PWM, WDTumber of I/O36rogram Memory SizeI6KB (8K x 16)rogram Memory TypeFLASHEPROM Size256 x 8AM Size768 x 8roltage - Supply (Vcc/Vdd)4.2 V ~ 5.5 Vvaca ConvertersInternaluperating Temperature-40°C ~ 85°C (TA)uperating Temperature-40°C ~ 85°C (TA)uperature44-VQFN Exposed Pad	Core Processor	PIC
Onnectivity I2C, SPI, UART/USART eripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT fumber of I/O 36 rogram Memory Size 16KB (8K x 16) rogram Memory Type FLASH EPROM Size 256 x 8 AM Size 768 x 8 roltage - Supply (Vcc/Vdd) 4.2 V ~ 5.5 V vaca Converters A/D 13x12b rescillator Type -40°C ~ 85°C (TA) routing Type -44-VQFN Exposed Pad	Core Size	8-Bit
Brown-out Detect/Reset, HLVD, POR, PWM, WDT fumber of I/O 36 rogram Memory Size 16KB (8K x 16) rogram Memory Type FLASH EPROM Size 256 x 8 AM Size 768 x 8 foltage - Supply (Vcc/Vdd) 4.2 V ~ 5.5 V scillator Type Internal sperating Temperature -40°C ~ 85°C (TA) founting Type 44-VQFN Exposed Pad	Speed	40MHz
Yumber of I/O 36 rogram Memory Size 16KB (8K x 16) rogram Memory Type FLASH EPROM Size 256 x 8 AM Size 768 x 8 foltage - Supply (Vcc/Vdd) 4.2 V ~ 5.5 V vata Converters A/D 13x12b scillator Type -40°C ~ 85°C (TA) outning Type - ackage / Case 44-VQFN Exposed Pad	Connectivity	I2C, SPI, UART/USART
rogram Memory Size16KB (8K x 16)rogram Memory TypeFLASHEPROM Size256 x 8AM Size768 x 8oltage - Supply (Vcc/Vdd)4.2 V ~ 5.5 Vata ConvertersA/D 13x12bscillator TypeInternalperating Temperature-40°C ~ 85°C (TA)ounting Type-ackage / Case44-VQFN Exposed Pad	Peripherals	Brown-out Detect/Reset, HLVD, POR, PWM, WDT
FLASH EPROM Size 256 x 8 AM Size 768 x 8 oltage - Supply (Vcc/Vdd) 4.2 V ~ 5.5 V ata Converters A/D 13x12b scillator Type Internal operating Temperature -40°C ~ 85°C (TA) dounting Type - ackage / Case 44-VQFN Exposed Pad	Number of I/O	36
EPROM Size256 x 8AM Size768 x 8foltage - Supply (Vcc/Vdd)4.2 V ~ 5.5 Vata ConvertersA/D 13x12bscillator TypeInternaluperating Temperature-40°C ~ 85°C (TA)Iounting Type-ackage / Case44-VQFN Exposed Pad	Program Memory Size	16KB (8K x 16)
AM Size 768 x 8 oltage - Supply (Vcc/Vd) 4.2 V ~ 5.5 V ata Converters A/D 13x12b scillator Type Internal operating Temperature -40°C ~ 85°C (TA) founting Type - ackage / Case 44-VQFN Exposed Pad	Program Memory Type	FLASH
ioltage - Supply (Vcc/Vdd)4.2 V ~ 5.5 Vata ConvertersA/D 13x12bscillator TypeInternaloperating Temperature-40°C ~ 85°C (TA)Iounting Type-ackage / Case44-VQFN Exposed Pad	EEPROM Size	256 x 8
AverageAvera	RAM Size	768 x 8
scillator TypeInternaluperating Temperature-40°C ~ 85°C (TA)Iounting Type-ackage / Case44-VQFN Exposed Pad	Voltage - Supply (Vcc/Vdd)	4.2 V ~ 5.5 V
perating Temperature-40°C ~ 85°C (TA)Iounting Type-ackage / Case44-VQFN Exposed Pad	Data Converters	A/D 13x12b
Iounting Type - ackage / Case 44-VQFN Exposed Pad	Oscillator Type	Internal
ackage / Case 44-VQFN Exposed Pad	Operating Temperature	-40°C ~ 85°C (TA)
	Mounting Type	-
upplier Device Package 44-OFN (8x8)	Package / Case	44-VQFN Exposed Pad
	Supplier Device Package	44-QFN (8x8)
Report errors?		Report errors?

PIC18F4423-I/ML Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

PIC18F4423-I/ML Payment Methods



PIC18F4423-I/ML Shipping Methods



If you have any question about PIC18F4423-I/ML, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com