

PIC24F32KA301-E/SS

PIC24F32KA301-E/SS Information



For Reference Only

Part Number PIC24F32KA301-E/SS

Manufacturer Microchip Technology

Category Integrated Circuits (ICs)
Embedded - Microcontrollers

Description IC MCU 16BIT 32KB FLASH 20SSOP **Package** 20-SSOP (0.209", 5.30mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PIC24F32KA301-E/SS Specifications

Manufacturer Part NumberPIC24F32KA301-E/SSManufacturerMicrochip TechnologyCategoryIntegrated Circuits (ICs)Embedded - MicrocontrollersPackage20-SSOP (0.209", 5.30mm Width)SeriesPIC? XLP? 24FCore ProcessorPICCore Size16-BitSpeed32MHzConnectivityI2C, IrDA, LIN, SPI, UART/USARTPeripheralsBrown-out Detect/Reset, HLVD, POR, PWM, WDTNumber of I/O18Program Memory Size32KB (11K x 24)Program Memory TypeFLASHEEPROM Size512 x 8RAM Size2K x 8Voltage - Supply (Vcc/Vdd)1.8 V ~ 3.6 V
Category Integrated Circuits (ICs) Embedded - Microcontrollers Package 20-SSOP (0.209", 5.30mm Width) Series PIC? XLP? 24F Core Processor PIC Core Size 16-Bit Speed 32MHz Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O 18 Program Memory Size 32KB (11K x 24) Program Memory Type FLASH EEPROM Size 512 x 8 RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 1.8 V ~ 3.6 V
Embedded - Microcontrollers Package 20-SSOP (0.209", 5.30mm Width) Series PIC? XLP? 24F Core Processor PIC Core Size 16-Bit Speed 32MHz Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O 18 Program Memory Size 32KB (11K x 24) Program Memory Type FLASH EEPROM Size 512 x 8 RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 1.8 V ~ 3.6 V
Package 20-SSOP (0.209", 5.30mm Width) Series PIC? XLP? 24F Core Processor PIC Core Size 16-Bit Speed 32MHz Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O 18 Program Memory Size 32KB (11K x 24) Program Memory Type FLASH EEPROM Size 512 x 8 RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 1.8 V ~ 3.6 V
$\begin{array}{cccccccccccccccccccccccccccccccccccc$
Core Processor Core Size 16-Bit Speed 32MHz Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O 18 Program Memory Size 32KB (11K x 24) Program Memory Type FLASH EEPROM Size 712 x 8 RAM Size Voltage - Supply (Vcc/Vdd) PIC 16-Bit 32MHz 12C, IrDA, LIN, SPI, UART/USART Brown-out Detect/Reset, HLVD, POR, PWM, WDT 18 Program Memory Size 32KB (11K x 24) FLASH EEPROM Size 11.8 V ~ 3.6 V
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$
Speed 32MHz Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O 18 Program Memory Size 32KB (11K x 24) Program Memory Type FLASH EEPROM Size 512 x 8 RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 1.8 V ~ 3.6 V
Connectivity I2C, IrDA, LIN, SPI, UART/USART Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O 18 Program Memory Size 32KB (11K x 24) Program Memory Type FLASH EEPROM Size 512 x 8 RAM Size Voltage - Supply (Vcc/Vdd) 1.8 V ~ 3.6 V
Peripherals Brown-out Detect/Reset, HLVD, POR, PWM, WDT Number of I/O 18 Program Memory Size 32KB (11K x 24) Program Memory Type FLASH EEPROM Size 512 x 8 RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) $1.8 \text{ V} \sim 3.6 \text{ V}$
Number of I/O 18 Program Memory Size 32KB (11K x 24) Program Memory Type FLASH EEPROM Size 512 x 8 RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 1.8 V ~ 3.6 V
Program Memory Size $32KB (11K \times 24)$ Program Memory Type FLASH EEPROM Size 512×8 RAM Size $2K \times 8$ Voltage - Supply (Vcc/Vdd) $1.8 \text{ V} \sim 3.6 \text{ V}$
Program Memory Type FLASH EEPROM Size 512 x 8 RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) $1.8 \text{ V} \sim 3.6 \text{ V}$
EEPROM Size 512×8 RAM Size $2K \times 8$ Voltage - Supply (Vcc/Vdd) $1.8 \text{ V} \sim 3.6 \text{ V}$
RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 1.8 V ~ 3.6 V
Voltage - Supply (Vcc/Vdd) $1.8 \text{ V} \sim 3.6 \text{ V}$
Data Converters A/D 12x12b
Oscillator Type Internal
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C} \text{ (TA)}$
Mounting Type -
Package / Case 20-SSOP (0.209", 5.30mm Width)
Supplier Device Package 20-SSOP
Report error

PIC24F32KA301-E/SS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PIC24F32KA301-E/SS Payment Methods



















PIC24F32KA301-E/SS Shipping Methods













If you have any question about PIC24F32KA301-E/SS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com