

PJ1-022 Information

Part Number PJ1-022
Manufacturer CUI Inc.

Category Connectors, Interconnects Barrel - Power Connectors

Description CONN PWR JACK 0.7X2.35MM SOLDER

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PJ1-022 Specifications

Manufacturer Part NumberPII-022ManufacturerCUI Inc.CategoryConnectors, InterconnectsBarrel - Power ConnectorsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter0.70mm ID (0.028"), 2.35mm OD (0.093") EIAJ-1Actual Diameter0.026" (0.65mm ID), 0.110" (2.80mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeThrough Hole, Right AngleMounting Feature-TerminationSolderShieldingUnshieldedFeaturesBoard GuideInsulation Color-Voltage - Rated24VDCCurrent Rating1A		
Category Connectors, Interconnects Barrel - Power Connectors Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 0.70mm ID (0.028"), 2.35mm OD (0.093") EIAJ-1 Actual Diameter 0.026" (0.65mm ID), 0.110" (2.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole, Right Angle Mounting Feature - Termination Solder Shielding Unshielded Features Board Guide Insulation Color - Voltage - Rated Connectors Interconnects Actual Power Connectors - Connectors Conn	Manufacturer Part Number	PJ1-022
Barrel - Power Connectors Package Series Connector Type Jack Gender Male Industry Recognized Mating Diameter 0.70mm ID (0.028"), 2.35mm OD (0.093") EIAJ-1 Actual Diameter 0.026" (0.65mm ID), 0.110" (2.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole, Right Angle Mounting Feature - Termination Solder Shielding Unshielded Features Board Guide Insulation Color - Voltage - Rated 24VDC	Manufacturer	CUI Inc.
Package - Connector Type Jack Gender Male Industry Recognized Mating Diameter 0.70mm ID (0.028"), 2.35mm OD (0.093") EIAJ-1 Actual Diameter 0.026" (0.65mm ID), 0.110" (2.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole, Right Angle Mounting Feature - Termination Solder Shielding Unshielded Features Board Guide Insulation Color - Voltage - Rated 24VDC	Category	Connectors, Interconnects
Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 0.70mm ID (0.028"), 2.35mm OD (0.093") EIAJ-1 Actual Diameter 0.026" (0.65mm ID), 0.110" (2.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole, Right Angle Mounting Feature - Termination Solder Shielding Unshielded Features Board Guide Insulation Color - Voltage - Rated 24VDC		Barrel - Power Connectors
Connector Type Gender Male Industry Recognized Mating Diameter 0.70mm ID (0.028"), 2.35mm OD (0.093") EIAJ-1 Actual Diameter 0.026" (0.65mm ID), 0.110" (2.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole, Right Angle Mounting Feature - Termination Solder Shielding Unshielded Features Board Guide Insulation Color Voltage - Rated Jack Male 1.700000000000000000000000000000000000	Package	-
Gender Male Industry Recognized Mating Diameter 0.70mm ID (0.028"), 2.35mm OD (0.093") EIAJ-1 Actual Diameter 0.026" (0.65mm ID), 0.110" (2.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole, Right Angle Mounting Feature - Termination Solder Shielding Unshielded Features Board Guide Insulation Color - Voltage - Rated 24VDC	Series	-
Industry Recognized Mating Diameter 0.70mm ID (0.028"), 2.35mm OD (0.093") EIAJ-1 Actual Diameter 0.026" (0.65mm ID), 0.110" (2.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole, Right Angle Mounting Feature - Termination Solder Shielding Unshielded Features Board Guide Insulation Color - Voltage - Rated 24VDC	Connector Type	Jack
Actual Diameter 0.026" (0.65mm ID), 0.110" (2.80mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole, Right Angle Mounting Feature - Termination Solder Shielding Unshielded Features Board Guide Insulation Color - Voltage - Rated 24VDC	Gender	Male
Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeThrough Hole, Right AngleMounting Feature-TerminationSolderShieldingUnshieldedFeaturesBoard GuideInsulation Color-Voltage - Rated24VDC	Industry Recognized Mating Diameter	0.70mm ID (0.028"), 2.35mm OD (0.093") EIAJ-1
Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole, Right Angle - Termination Solder Shielding Unshielded Features Board Guide Insulation Color Voltage - Rated Single Switch, Normally Closed - Language Language - Language Shielding Language	Actual Diameter	0.026" (0.65mm ID), 0.110" (2.80mm OD)
Mounting Type Mounting Feature Termination Solder Unshielded Features Board Guide Insulation Color Voltage - Rated Through Hole, Right Angle - Unshielded 24VDC	Number of Positions/Contacts	2 Conductors, 3 Contacts
Mounting Feature-TerminationSolderShieldingUnshieldedFeaturesBoard GuideInsulation Color-Voltage - Rated24VDC	Internal Switch(s)	Single Switch, Normally Closed
Termination Solder Shielding Unshielded Features Board Guide Insulation Color - Voltage - Rated 24VDC	Mounting Type	Through Hole, Right Angle
Shielding Unshielded Features Board Guide Insulation Color - Voltage - Rated 24VDC	Mounting Feature	-
Features Board Guide Insulation Color - Voltage - Rated 24VDC	Termination	Solder
Insulation Color - Voltage - Rated 24VDC	Shielding	Unshielded
Voltage - Rated 24VDC	Features	Board Guide
	Insulation Color	-
Current Rating 1A	Voltage - Rated	24VDC
	Current Rating	1A
Report errors?		Report errors?

PJ1-022 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PJ1-022 Payment Methods



















PJ1-022 Shipping Methods













If you have any question about PJ1-022, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com