

PLC3G822C04 Information



For Reference Only

Part Number PLC3G822C04 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT FMALE 4POS GOLD SLDR

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PLC3G822C04 Specifications

Manufacturer Part Number Manufacturer Category Connectors, Interconnects Circular Connectors Package - Series PL Connector Type Receptacle, Female Sockets Number of Positions Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Fastening Type Latch Lock, Push-Pull Orientation C Ingress Protection Ingress Protection Shell Material, Finish Contact Finish Polysulfone (PSU) Contact Finish Voltage - Rated Current Rating Perpent agrees Perpent agrees Perpent agrees Perpent agrees Perpent agrees Perpent agrees		
Category Connectors, Interconnects Circular Connectors Package - Series PL Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Fastening Type Latch Lock, Push-Pull Orientation C Ingress Protection Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Strain Relief Nut Voltage - Rated Current Rating Series Connectors, Interconnects Circular Connectors Connectors Receptacle, Female Sockets A C C Connector Type Lacch Lock, Pemale Sockets Free Hanging (In-Line) Free Hanging (In-Line) Free Hanging (In-Line) Free Hanging (In-Line) Solder Cup Latch Lock, Push-Pull Contact Finish Polysulfone (PSU) Contact Finish Strain Relief Nut Voltage - Rated - Current Rating	Manufacturer Part Number	PLC3G822C04
Package - Series PL Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert - Shell Size, MIL - Solder Cup Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation C C Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Strain Relief Nut Voltage - Rated Current Rating 8A	Manufacturer	ITT Cannon, LLC
Package-SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch Lock, Push-PullOrientationCIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeaturesStrain Relief NutVoltage - Rated-Current Rating8A	Category	Connectors, Interconnects
Series PL Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation C Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Strain Relief Nut Voltage - Rated - Current Rating 8A		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation C Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Strain Relief Nut Voltage - Rated - Current Rating 8A	Package	-
Number of Positions Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation C Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Features Strain Relief Nut Voltage - Rated Current Rating 8A	Series	PL
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation C Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Strain Relief Nut Voltage - Rated Current Rating 8A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation C Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Strain Relief Nut Voltage - Rated Current Rating 8A	Number of Positions	4
Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation C Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Strain Relief Nut Voltage - Rated - Current Rating 8A	Shell Size - Insert	-
Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation C Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Strain Relief Nut Voltage - Rated - Current Rating 8A	Shell Size, MIL	-
Fastening Type Crientation C Ingress Protection Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Strain Relief Nut Voltage - Rated Current Rating Latch Lock, Push-Pull C C Current Rating Latch Lock, Push-Pull C A A A B A A Strain Pull A B A A B A B A B A B A B A B A B A B A B B	Mounting Type	Free Hanging (In-Line)
Orientation C Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Strain Relief Nut Voltage - Rated - Current Rating 8A	Termination	Solder Cup
Ingress Protection Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Strain Relief Nut Voltage - Rated Current Rating 8A	Fastening Type	Latch Lock, Push-Pull
Shell Material, Finish Contact Finish Gold Features Strain Relief Nut Voltage - Rated Current Rating Polysulfone (PSU) Gold Strain Relief Nut	Orientation	С
Contact Finish Gold Features Strain Relief Nut Voltage - Rated Current Rating 8A	Ingress Protection	IP50 - Dust Protected
Features Strain Relief Nut Voltage - Rated - Current Rating 8A	Shell Material, Finish	Polysulfone (PSU)
Voltage - Rated - Current Rating 8A	Contact Finish	Gold
Current Rating 8A	Features	Strain Relief Nut
-	Voltage - Rated	-
Papart arrors?	Current Rating	8A
Report errors:		Report errors?

PLC3G822C04 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PLC3G822C04 Payment Methods





















PLC3G822C04 Shipping Methods













If you have any question about PLC3G822C04, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com