

PS2562-1-V-A Information

Part Number PS2562-1-V-A

Manufacturer CEL
Category Isolators

Optoisolators - Transistor, Photovoltaic Output

Description OPTOISOLATOR 5KV DARL 4DIP

4-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.

Package









PS2562-1-V-A Specifications

Number of Channels	1
Number of Channels	1
Voltage - Isolation	5000Vrms
Current Transfer Ratio (Min)	200% @ 1mA
Current Transfer Ratio (Max)	-
Turn On / Turn Off Time (Typ)	-
Rise / Fall Time (Typ)	100μs, 100μs
Input Type	DC
Output Type	Darlington
Voltage - Output (Max)	40V
Current - Output / Channel	200mA
Voltage - Forward (Vf) (Typ)	1.17V
Current - DC Forward (If) (Max)	80mA
Vce Saturation (Max)	1V
Operating Temperature	-55°C ~ 100°C
Mounting Type	Through Hole
Package / Case	4-DIP (0.300", 7.62mm)
Supplier Device Package	4-DIP
	Report errors?

PS2562-1-V-A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PS2562-1-V-A Payment Methods



















PS2562-1-V-A Shipping Methods













If you have any question about PS2562-1-V-A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com