

PSAA18U-120-R-CR5

PSAA18U-120-R-CR5 Information

Heisener.com

Part Number PSAA18U-120-R-CR5

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 12V 18W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSAA18U-120-R-CR5 Specifications

Manufacturer Part Number PSAA18U-120-R-CRS Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSAA18U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesPSAA18URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)1.5APower (Watts)18WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mmSize / Dimension4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Manufacturer Part Number	PSAA18U-120-R-CR5
Package - Series PSAA18U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Manufacturer	Phihong USA
Package - Series PSAA18U Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSAA18URegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)1.5APower (Watts)18WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mmSize / Dimension4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Series	PSAA18U
Input TypeCord (Sold Separately)Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption 300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 4.06° L x 1.93° W x 1.32° H (103.0mm x 49.0mm x 33.5mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption 300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 4.06° L x 1.93° W x 1.32° H (103.0mm x 49.0mm x 33.5mm)	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 1.5A Power (Watts) No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 40°C Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 12V 12V 12V 12V 12V 12V 12V 12	Input Type	Cord (Sold Separately)
Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $18W$ No Load Power Consumption $300mW$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug R/A, $0.7mm$ I.D. x $2.5mm$ O.D. x $10.0mm$ Size / Dimension 4.06 " L x 1.93 " W x 1.32 " H ($103.0mm$ x $49.0mm$ x $33.5mm$)	Voltage - Output	12V
No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 4.06° L x 1.93° W x 1.32° H (103.0mm x 49.0mm x 33.5mm)	Current - Output (Max)	1.5A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension $4.06^{\circ}\text{L} \times 1.93^{\circ}\text{W} \times 1.32^{\circ}\text{H} (103.0 \text{mm} \times 49.0 \text{mm} \times 33.5 \text{mm})$	Power (Watts)	18W
Applications ITE (Commercial) Efficiency Level V Operating Temperature 0° C ~ 40° C Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 4.06° L x 1.93° W x 1.32° H (103.0 mm x 49.0 mm x 33.5 mm)	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension $4.06^{\circ}\text{L} \times 1.93^{\circ}\text{W} \times 1.32^{\circ}\text{H} (103.0 \text{mm} \times 49.0 \text{mm} \times 33.5 \text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension $4.06^{\circ}\text{L} \text{ x } 1.93^{\circ}\text{ W x } 1.32^{\circ}\text{H} (103.0\text{mm x } 49.0\text{mm x } 33.5\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Efficiency	Level V
Size / Dimension 4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug R/A, 0.7mm I.D. x 2.5mm O.D. x 10.0mm
Report errors?	Size / Dimension	4.06" L x 1.93" W x 1.32" H (103.0mm x 49.0mm x 33.5mm)
		Report errors?

PSAA18U-120-R-CR5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSAA18U-120-R-CR5 Payment Methods





















PSAA18U-120-R-CR5 Shipping Methods













If you have any question about PSAA18U-120-R-CR5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com