



# **QBLP674-IWM-NW Information**

Part NumberQBLP674-IWM-NWManufacturerQT Brightek (QTB)CategoryOptoelectronics

LED Indication - Discrete

**Description** LED NEUTRAL WHITE 4000K 2SMD

Package 2-SMD, Flat Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



### **Certified Quality**

www.heisener.com

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **QBLP674-IWM-NW Specifications**

Manufacturer Part Number         QBLP674-IWM-NW           Manufacturer         QT Brightek (QTB)           Category         Optoelectronics           LED Indication - Discrete           Package         2-SMD, Flat Lead           Series         -           Color         White           Configuration         -           Lens Color         -           Lens Transparency         -           Millicandela Rating         3400mcd           Lens Style/Size         Oval with Flat Top           Voltage - Forward (Vf) (Typ)         3.2V           Current - Test         30mA           Viewing Angle         120°           Mounting Type         Surface Mount           Wavelength - Dominant         4000K           Wavelength - Peak         -           Features         -           Package / Case         2-SMD, Flat Lead           Supplier Device Package         2-PLCC           Size / Dimension         2.80mm L x 1.40mm W           Height (Max)         0.85mm		
Category         Optoelectronics           Package         2-SMD, Flat Lead           Series         -           Color         White           Configuration         -           Lens Color         -           Lens Transparency         -           Millicandela Rating         3400mcd           Lens Style/Size         Oval with Flat Top           Voltage - Forward (Vf) (Typ)         3.2V           Current - Test         30mA           Viewing Angle         120°           Mounting Type         Surface Mount           Wavelength - Dominant         4000K           Wavelength - Peak         -           Features         -           Package / Case         2-SMD, Flat Lead           Supplier Device Package         2-PLCC           Size / Dimension         2.80mm L x 1.40mm W           Height (Max)         0.85mm	Manufacturer Part Number	QBLP674-IWM-NW
Package         2-SMD, Flat Lead           Series         -           Color         White           Configuration         -           Lens Color         -           Lens Transparency         -           Millicandela Rating         3400mcd           Lens Style/Size         Oval with Flat Top           Voltage - Forward (Vf) (Typ)         3.2V           Current - Test         30mA           Viewing Angle         120°           Mounting Type         Surface Mount           Wavelength - Dominant         4000K           Wavelength - Peak         -           Features         -           Package / Case         2-SMD, Flat Lead           Supplier Device Package         2-PLCC           Size / Dimension         2.80mm L x 1.40mm W           Height (Max)         0.85mm	Manufacturer	QT Brightek (QTB)
Package         2-SMD, Flat Lead           Series         -           Color         White           Configuration         -           Lens Color         -           Lens Transparency         -           Millicandela Rating         3400mcd           Lens Style/Size         Oval with Flat Top           Voltage - Forward (Vf) (Typ)         3.2V           Current - Test         30mA           Viewing Angle         120°           Mounting Type         Surface Mount           Wavelength - Dominant         4000K           Wavelength - Peak         -           Features         -           Package / Case         2-SMD, Flat Lead           Supplier Device Package         2-PLCC           Size / Dimension         2.80mm L x 1.40mm W           Height (Max)         0.85mm	Category	Optoelectronics
Series         -           Color         White           Configuration         -           Lens Color         -           Lens Transparency         -           Millicandela Rating         3400mcd           Lens Style/Size         Oval with Flat Top           Voltage - Forward (Vf) (Typ)         3.2V           Current - Test         30mA           Viewing Angle         120°           Mounting Type         Surface Mount           Wavelength - Dominant         4000K           Wavelength - Peak         -           Features         -           Package / Case         2-SMD, Flat Lead           Supplier Device Package         2-PLCC           Size / Dimension         2.80mm L x 1.40mm W           Height (Max)         0.85mm		LED Indication - Discrete
Color         White           Configuration         -           Lens Color         -           Lens Transparency         -           Millicandela Rating         3400mcd           Lens Style/Size         Oval with Flat Top           Voltage - Forward (Vf) (Typ)         3.2V           Current - Test         30mA           Viewing Angle         120°           Mounting Type         Surface Mount           Wavelength - Dominant         4000K           Wavelength - Peak         -           Features         -           Package / Case         2-SMD, Flat Lead           Supplier Device Package         2-PLCC           Size / Dimension         2.80mm L x 1.40mm W           Height (Max)         0.85mm	Package	2-SMD, Flat Lead
Configuration - Clens Color - Clens Transparency - Millicandela Rating 3400mcd - Clens Style/Size Oval with Flat Top  Voltage - Forward (Vf) (Typ) 3.2V  Current - Test 30mA  Viewing Angle 120°  Mounting Type Surface Mount  Wavelength - Dominant 4000K  Wavelength - Peak - Features - Package / Case 2-SMD, Flat Lead  Supplier Device Package 2-PLCC  Size / Dimension 2.80mm L x 1.40mm W  Height (Max) 0.85mm	Series	-
Lens Color-Lens Transparency-Millicandela Rating3400mcdLens Style/SizeOval with Flat TopVoltage - Forward (Vf) (Typ)3.2VCurrent - Test30mAViewing Angle120°Mounting TypeSurface MountWavelength - Dominant4000KWavelength - Peak-Features-Package / Case2-SMD, Flat LeadSupplier Device Package2-PLCCSize / Dimension2.80mm L x 1.40mm WHeight (Max)0.85mm	Color	White
Lens Transparency-Millicandela Rating3400mcdLens Style/SizeOval with Flat TopVoltage - Forward (Vf) (Typ)3.2VCurrent - Test30mAViewing Angle120°Mounting TypeSurface MountWavelength - Dominant4000KWavelength - Peak-Features-Package / Case2-SMD, Flat LeadSupplier Device Package2-PLCCSize / Dimension2.80mm L x 1.40mm WHeight (Max)0.85mm	Configuration	-
Millicandela Rating  Lens Style/Size  Oval with Flat Top  Voltage - Forward (Vf) (Typ)  3.2V  Current - Test  30mA  Viewing Angle  120°  Mounting Type  Surface Mount  Wavelength - Dominant  4000K  Wavelength - Peak	Lens Color	-
Lens Style/SizeOval with Flat TopVoltage - Forward (Vf) (Typ)3.2VCurrent - Test30mAViewing Angle120°Mounting TypeSurface MountWavelength - Dominant4000KWavelength - Peak-Features-Package / Case2-SMD, Flat LeadSupplier Device Package2-PLCCSize / Dimension2.80mm L x 1.40mm WHeight (Max)0.85mm	Lens Transparency	-
Voltage - Forward (Vf) (Typ)  Current - Test  30mA  Viewing Angle  120°  Mounting Type  Surface Mount  Wavelength - Dominant  4000K  Wavelength - Peak	Millicandela Rating	3400mcd
Current - Test 30mA  Viewing Angle 120°  Mounting Type Surface Mount  Wavelength - Dominant 4000K  Wavelength - Peak - Features - Package / Case 2-SMD, Flat Lead  Supplier Device Package 2-PLCC  Size / Dimension 2.80mm L x 1.40mm W  Height (Max) 0.85mm	Lens Style/Size	Oval with Flat Top
Viewing Angle120°Mounting TypeSurface MountWavelength - Dominant4000KWavelength - Peak-Features-Package / Case2-SMD, Flat LeadSupplier Device Package2-PLCCSize / Dimension2.80mm L x 1.40mm WHeight (Max)0.85mm	Voltage - Forward (Vf) (Typ)	3.2V
Mounting Type Surface Mount  Wavelength - Dominant 4000K  Wavelength - Peak - Features - Package / Case 2-SMD, Flat Lead  Supplier Device Package 2-PLCC Size / Dimension 2.80mm L x 1.40mm W  Height (Max) 0.85mm	Current - Test	30mA
Wavelength - Dominant  Wavelength - Peak  Features  - Package / Case  Supplier Device Package  Size / Dimension  Height (Max)  4000K	Viewing Angle	120°
Wavelength - Peak - Features - Package / Case 2-SMD, Flat Lead Supplier Device Package 2-PLCC Size / Dimension 2.80mm L x 1.40mm W Height (Max) 0.85mm	Mounting Type	Surface Mount
Features - Package / Case 2-SMD, Flat Lead Supplier Device Package 2-PLCC Size / Dimension 2.80mm L x 1.40mm W Height (Max) 0.85mm	Wavelength - Dominant	4000K
Package / Case2-SMD, Flat LeadSupplier Device Package2-PLCCSize / Dimension2.80mm L x 1.40mm WHeight (Max)0.85mm	Wavelength - Peak	-
Supplier Device Package 2-PLCC Size / Dimension 2.80mm L x 1.40mm W Height (Max) 0.85mm	Features	-
Size / Dimension         2.80mm L x 1.40mm W           Height (Max)         0.85mm	Package / Case	2-SMD, Flat Lead
Height (Max) 0.85mm	Supplier Device Package	2-PLCC
	Size / Dimension	2.80mm L x 1.40mm W
Report errors?	Height (Max)	0.85mm
		Report errors?

### **QBLP674-IWM-NW Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **QBLP674-IWM-NW Payment Methods**



















# **QBLP674-IWM-NW Shipping Methods**













If you have any question about QBLP674-IWM-NW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com