

RAPC722 Information

Heisener.com

For Reference Only

Part Number RAPC722

Manufacturer Switchcraft Inc.

Category

Connectors, Interconnects

Barrel - Power Connectors

Description

CONN PWR JACK 2X5.5MM SOLDER

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RAPC722 Specifications

Manufacturer Part Number RAPC722 Manufacturer Switchcraft Inc. Category Connectors, Interconnects Barrel - Power Connectors Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.00mm ID (0.079"), 5.50mm OD (0.217") Actual Diameter 0.078" (2.00mm ID), 0.248" (6.30mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole, Right Angle Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated - Current Rating 5A		
CategoryConnectors, InterconnectsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter2.00mm ID (0.079"), 5.50mm OD (0.217")Actual Diameter0.078" (2.00mm ID), 0.248" (6.30mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeThrough Hole, Right AngleMounting Feature-TerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated-Current Rating5A	Manufacturer Part Number	RAPC722
Package - Connector Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.00mm ID (0.079"), 5.50mm OD (0.217") Actual Diameter 0.078" (2.00mm ID), 0.248" (6.30mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole, Right Angle Mounting Feature - Fermination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated Current Rating 5A	Manufacturer	Switchcraft Inc.
Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.00mm ID (0.079"), 5.50mm OD (0.217") Actual Diameter 0.078" (2.00mm ID), 0.248" (6.30mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole, Right Angle Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated Current Rating 5A	Category	Connectors, Interconnects
Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.00mm ID (0.079"), 5.50mm OD (0.217") Actual Diameter 0.078" (2.00mm ID), 0.248" (6.30mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole, Right Angle Mounting Feature - Fermination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated - Current Rating 5A		Barrel - Power Connectors
Connector Type Gender Male Industry Recognized Mating Diameter 2.00mm ID (0.079"), 5.50mm OD (0.217") Actual Diameter 0.078" (2.00mm ID), 0.248" (6.30mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole, Right Angle Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color Voltage - Rated Current Rating Jack Male Angle Male London ID (0.079"), 5.50mm OD (0.217") London ID (0.079"), 5.50mm OD (0	Package	-
Gender Male Industry Recognized Mating Diameter 2.00mm ID (0.079"), 5.50mm OD (0.217") Actual Diameter 0.078" (2.00mm ID), 0.248" (6.30mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole, Right Angle Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated - Current Rating 5A	Series	-
Industry Recognized Mating Diameter 2.00mm ID (0.079"), 5.50mm OD (0.217") Actual Diameter 0.078" (2.00mm ID), 0.248" (6.30mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole, Right Angle Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color Voltage - Rated Current Rating 5 A	Connector Type	Jack
Actual Diameter 0.078" (2.00mm ID), 0.248" (6.30mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole, Right Angle Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated - Current Rating 5A	Gender	Male
Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeThrough Hole, Right AngleMounting Feature-TerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated-Current Rating5A	Industry Recognized Mating Diameter	2.00mm ID (0.079"), 5.50mm OD (0.217")
Internal Switch(s) Single Switch, Normally Closed Mounting Type Through Hole, Right Angle - Termination Solder Eyelet(s) Unshielded Features - Insulation Color Voltage - Rated Current Rating Single Switch, Normally Closed Through Hole, Right Angle - Unshielded - Solder Eyelet(s) Unshielded - Solder Eyelet(s) Shielding Solder Eyelet(s) Solder Eyelet(s)	Actual Diameter	0.078" (2.00mm ID), 0.248" (6.30mm OD)
Mounting Type Mounting Feature Termination Solder Eyelet(s) Shielding Unshielded Features Insulation Color Voltage - Rated Current Rating Through Hole, Right Angle - Current Rating Through Hole, Right Angle - Solder Eyelet(s) Unshielded - Solder Eyelet(s) Unshielded 5A	Number of Positions/Contacts	2 Conductors, 3 Contacts
Mounting Feature Termination Solder Eyelet(s) Unshielded Features - Insulation Color Voltage - Rated Current Rating 5A	Internal Switch(s)	Single Switch, Normally Closed
Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color - Voltage - Rated - Current Rating 5A	Mounting Type	Through Hole, Right Angle
Shielding Unshielded Features - Insulation Color - Voltage - Rated - Current Rating 5A	Mounting Feature	-
Features - Insulation Color - Voltage - Rated - Current Rating 5A	Termination	Solder Eyelet(s)
Insulation Color - Voltage - Rated - Current Rating 5A	Shielding	Unshielded
Voltage - Rated - Current Rating 5A	Features	-
Current Rating 5A	Insulation Color	-
	Voltage - Rated	-
Report errors?	Current Rating	5A
		Report errors?

RAPC722 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RAPC722 Payment Methods

































If you have any question about RAPC722, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com