

RER40F1001MCSL

RER40F1001MCSL Information

Heisener.com

Part Number RER40F1001MCSL

Manufacturer Vishay Dale Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 1K OHM 1% 5W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RER40F1001MCSL Specifications

Manufacturer Part NumberRER40F1001MCSLManufacturerVishay DaleCategoryResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER40Resistance1 kOhmsTolerance±1%Power (Watts)5WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)		
Category Resistors Package Axial, Box Series Military, MIL-PRF-39009, RER40 Resistance 1 kOhms Tolerance ±1% Power (Watts) 5W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Manufacturer Part Number	RER40F1001MCSL
Chassis Mount Resistors Package Axial, Box Military, MIL-PRF-39009, RER40 Resistance 1 kOhms Tolerance ±1% Power (Watts) 5W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M(1%)	Manufacturer	Vishay Dale
PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER40Resistance1 kOhmsTolerance±1%Power (Watts)5WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Category	Resistors
SeriesMilitary, MIL-PRF-39009, RER40Resistance1 kOhmsTolerance±1%Power (Watts)5WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)		Chassis Mount Resistors
Resistance1 kOhmsTolerance±1%Power (Watts)5WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Package	Axial, Box
Tolerance ±1% Power (Watts) 5W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Series	Military, MIL-PRF-39009, RER40
Power (Watts) Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Package / Case Axial, Box Failure Rate M (1%)	Resistance	1 kOhms
CompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.600" L x 0.646" W (15.24mm x 16.41mm)Height - Seated (Max)0.335" (8.51mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Tolerance	±1%
Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Power (Watts)	5W
Operating Temperature -55°C ~ 250°C Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Composition	Wirewound
Features Military, Moisture Resistant, Non-Inductive Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Temperature Coefficient	±20ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Operating Temperature	-55°C ~ 250°C
Mounting Feature Flanges Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 1.24	Features	Military, Moisture Resistant, Non-Inductive
Size / Dimension 0.600" L x 0.646" W (15.24mm x 16.41mm) Height - Seated (Max) 0.335" (8.51mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate M (1%)	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate M (1%)	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RateM (1%)	Size / Dimension	0.600" L x 0.646" W (15.24mm x 16.41mm)
Package / Case Axial, Box Failure Rate M (1%)	Height - Seated (Max)	0.335" (8.51mm)
Failure Rate M (1%)	Lead Style	Solder Lugs
· ·	Package / Case	Axial, Box
Report errors?	Failure Rate	M (1%)
		Report errors?

RER40F1001MCSL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RER40F1001MCSL Payment Methods



















RER40F1001MCSL Shipping Methods













If you have any question about RER40F1001MCSL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com