

# RER50F28R7RCSL

### **RER50F28R7RCSL Information**

Heisener.com

Part Number RER50F28R7RCSL

Manufacturer Vishay Dale Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 28.7 OHM 1% 20W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **RER50F28R7RCSL Specifications**

Manufacturer Part NumberRER50F28R7RCSLManufacturerVishay DaleCategoryResistorsChassis Mount ResistorsPackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER50Resistance28.7 OhmsTolerance±1%Power (Watts)20WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-InductiveCoating, Housing TypeAluminum
Category  Resistors  Chassis Mount Resistors  Package  Axial, Box  Series  Military, MIL-PRF-39009, RER50  Resistance  28.7 Ohms  Tolerance  ±1%  Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±20ppm/°C  Operating Temperature  -55°C ~ 250°C  Features  Military, Moisture Resistant, Non-Inductive
Chassis Mount Resistors  Package Axial, Box  Series Military, MIL-PRF-39009, RER50  Resistance 28.7 Ohms  Tolerance ±1%  Power (Watts) 20W  Composition Wirewound  Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 250°C  Features Military, Moisture Resistant, Non-Inductive
PackageAxial, BoxSeriesMilitary, MIL-PRF-39009, RER50Resistance28.7 OhmsTolerance±1%Power (Watts)20WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-Inductive
SeriesMilitary, MIL-PRF-39009, RER50Resistance28.7 OhmsTolerance±1%Power (Watts)20WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 250°CFeaturesMilitary, Moisture Resistant, Non-Inductive
Resistance $28.7 \text{ Ohms}$ Tolerance $\pm 1\%$ Power (Watts) $20W$ CompositionWirewoundTemperature Coefficient $\pm 20 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ FeaturesMilitary, Moisture Resistant, Non-Inductive
Tolerance $\pm 1\%$ Power (Watts) $20W$ CompositionWirewoundTemperature Coefficient $\pm 20 \mathrm{ppm/^{\circ}C}$ Operating Temperature $-55^{\circ}\mathrm{C} \sim 250^{\circ}\mathrm{C}$ FeaturesMilitary, Moisture Resistant, Non-Inductive
Power (Watts) $20W$ CompositionWirewoundTemperature Coefficient $\pm 20 ppm/^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 250^{\circ}C$ FeaturesMilitary, Moisture Resistant, Non-Inductive
CompositionWirewoundTemperature Coefficient $\pm 20 \text{ppm/°C}$ Operating Temperature $-55 ^{\circ}\text{C} \sim 250 ^{\circ}\text{C}$ FeaturesMilitary, Moisture Resistant, Non-Inductive
Temperature Coefficient $\pm 20 \text{ppm}/^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ Features Military, Moisture Resistant, Non-Inductive
Operating Temperature $-55^{\circ}\text{C} \sim 250^{\circ}\text{C}$ Features Military, Moisture Resistant, Non-Inductive
Features Military, Moisture Resistant, Non-Inductive
• • • • • • • • • • • • • • • • • • • •
Coating Housing Type Aluminum
County, Housing Type
Mounting Feature Flanges
Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm)
Height - Seated (Max) 0.561" (14.25mm)
Lead Style Solder Lugs
Package / Case Axial, Box
Failure Rate R (0.01%)
Report errors?

#### **RER50F28R7RCSL Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **RER50F28R7RCSL Payment Methods**



















## **RER50F28R7RCSL Shipping Methods**













If you have any question about RER50F28R7RCSL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com