

RN55C1271BB14

uest a Quote

RN55C1271BB14 Information

	Part Number	RN55C1271BB14	
	Manufacturer	Vishay Dale	
www.tjellerny.com	Category	Resistors Through Hole Resistors	
	Description	RES 1.27K OHM 1/8W .1% AXIAL	- 5 E
	Package	Axial	
		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Req

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RN55C1271BB14 Specifications

Manufacturer Part NumberRN55C1271BB14ManufacturerVishay DaleCategoryResistorsThrough Hole ResistorsThrough Hole ResistorsPackageAxialSeriesMilitary, MIL-R-10509/7, RN55Resistance1.27 KOhmsTolerance±0.1%Power (Watts)0.125W, 1/8WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±050pm/°COperating Temperature-65°C ~ 175°C
CategoryResistorsThrough Hole ResistorsPackageAxialSeriesMilitary, MIL-R-10509/7, RN55Resistance1.27 kOhmsTolerance±0.1%Power (Watts)0.125W, 1/8WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTonperature Coefficient±50pm/°C
Through Hole ResistorsPackageAxialSeriesMilitary, MIL-R-10509/7, RN55Resistance1.27 kOhmsTolerance±0.1%Power (Watts)0.125W, 1/8WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°C
PackageAxialSeriesMilitary, MIL-R-10509/7, RN55Resistance1.27 kOhmsTolerance±0.1%Power (Watts)0.125W, 1/8WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°C
SeriesMilitary, MIL-R-10509/7, RN55Resistance1.27 kOhmsTolerance±0.1%Power (Watts)0.125W, 1/8WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°C
Resistance1.27 kOhmsTolerance±0.1%Power (Watts)0.125W, 1/8WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°C
Tolerance±0.1%Power (Watts)0.125W, 1/8WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°C
Power (Watts)0.125W, 1/8WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°C
CompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°C
FeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±50ppm/°C
Temperature Coefficient ±50ppm/°C
Operating Temperature $-65^{\circ}C \sim 175^{\circ}C$
operating reinperature 05 C 175 C
Package / Case Axial
Supplier Device Package Axial
Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)
Height - Seated (Max) -
Number of Terminations 2
Failure Rate -
Report errors?

RN55C1271BB14 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RN55C1271BB14 Payment Methods





If you have any question about RN55C1271BB14, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com