

RTX3-1AT-B006 Information



For Reference Only

Part Number RTX3-1AT-B006

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 16A 6V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RTX3-1AT-B006 Specifications

Manufacturer Part Number RTX3-1AT-B006 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series RTX, SCHRACK Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 108.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRTX, SCHRACKRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current108.3mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage250VAC - NomTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	RTX3-1AT-B006
Package-SeriesRTX, SCHRACKRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current108.3mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage250VAC - NomTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series RTX, SCHRACK Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 108.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesRTX, SCHRACKRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current108.3mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage250VAC - NomTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current108.3mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage250VAC - NomTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Latching, Single Coil Coil Current 108.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Series	RTX, SCHRACK
Coil Current108.3mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage250VAC - NomTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Coil Type	Latching, Single Coil
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Coil Current	108.3mA
Contact Rating (Current) Switching Voltage 250VAC - Nom Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) Operate Time - Release Time - Features Insulation - Class F Mounting Type Through Hole Termination Style 16A 250VAC - Nom 4.5 VDC - 1.5 VDC -	Coil Voltage	6VDC
Switching Voltage 250VAC - Nom Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) Operate Time Release Time - Release Time Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	16A
Turn Off Voltage (Min) Operate Time Release Time - Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC - Nom
Operate Time	Turn On Voltage (Max)	4.5 VDC
Release Time - Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Operate Time	-
Mounting Type Through Hole Termination Style PC Pin	Release Time	-
Termination Style PC Pin	Features	Insulation - Class F
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

RTX3-1AT-B006 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RTX3-1AT-B006 Payment Methods





















RTX3-1AT-B006 Shipping Methods













If you have any question about RTX3-1AT-B006, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com