

# **RWS600B48/CO2**

## **RWS600B48/CO2 Information**

whiseer.com		RWS600B48/CO2 TDK-Lambda Americas Inc. Power Supplies - External/Internal (Off-Board) AC DC Converters	
	Description	AC/DC CONVERTER 48V 600W	- <b>3321</b> 85-)
	Package	-	
		For the pricing/inventory/lead time, please contact	<b>III</b> 34754
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

#### For Reference Only

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **RWS600B48/CO2** Specifications

Manufacturer Part Number RWS600B48/CO2   Manufacturer TDK-Lambda Americas Inc.   Category Power Supplies - External/Internal (Off-Board)   ACDC Converters ACDC Converters   Package -   Series RWS-B   Type Enclosed   Number of Outputs 1   Voltage - Input 85 ~ 265 VAC   Voltage - Output 1 48V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Voltage - Output 4 -   Voltage - Output 5 -   Voltage - Output 6 -   Voltage - Output 7 -   Voltage - Output 4 -   Voltage - Output 4 -   Voltage - Soluti Maxi 600W   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 8%   Operating Temperature -0°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable, Universal Input   Mounting Type				
CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesRWS-BTypeEnclosedNumber of Outputs1Voltage - Input85 ~ 265 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Soltation-Voltage - Soltation-Voltage - Isolation-Voltage - Isolation-<	Manufacturer Part Number	RWS600B48/CO2		
AC DC converters   Package -   Series RWS-B   Type Enclosed   Number of Outputs 1   Voltage - Input 85 ~ 265 VAC   Voltage - Output 1 48V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Voltage - Solation 12.5A   Power (Watts) 600W   Applications TE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 88%   Operating Temperature -10°C ~ 0°C (With Derating)   Features Adjustable Output, DC Input Capable, Universal Input   Mounting Type Chassis Mount	Manufacturer	TDK-Lambda Americas Inc.		
Package-SeriesRWS-BTypeEnclosedNumber of Outputs1Voltage - Input85 ~ 265 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4-Voltage - Output 5600WCurrent - Output (Max)12.5APower (Watts)600WApplicationsITE (commercial)Voltage - Isolation8%Operating Temperature-0°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChasis MountSiz / Dimension7.4%" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Category	Power Supplies - External/Internal (Off-Board)		
SeriesRWS-BTypeEnclosedNumber of Outputs1Voltage - Input85 ~ 265 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4600WCurrent - Output (Max)12.5APower (Watts)600WApplicationsTTE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating TemperatureAdjustabe Output, DC Input Capable, Universal InputFeaturesAdjustabe Output, DC Input Capable, Universal InputMounting Type7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)		AC DC Converters		
TypeEnclosedNumber of Outputs1Voltage - Input85 ~ 265 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 412.5APower (Watts)60WApplications1FE (commercial)Voltage - Isolation8%Operating Temperature-0°C ~ 0°C (With Derating)FeaturesAdjustabe Output, DC Input Capable, Universal InputMounting Type7.48" L x 4.72" W x 2.40" H (190.0mm x 10.0mm)	Package	-		
Number of Outputs 1   Voltage - Input 85 ~ 265 VAC   Voltage - Output 1 48V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 12.5A   Power (Wats) 600W   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 88%   Operating Temperature -10°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable, Universal Input   Mounting Type Chasis Mount   Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Series	RWS-B		
Voltage - Input 85 ~ 265 VAC   Voltage - Output 1 48V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 12.5A   Power (Watts) 600W   Applications ITE (commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 88%   Operating Temperature Adjustable Output, DC Input Capable, Universal Input   Features Adjustable Output, DC Input Capable, Universal Input   Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Туре	Enclosed		
Voltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)12.5APower (Watts)600WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChasis MountSize / Dimension7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Number of Outputs	1		
Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 12.5A   Power (Watts) 600W   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 88%   Operating Temperature -10°C ~70°C (With Derating)   Features Adjustable Output, DC Input Capable, Universal Input   Mounting Type Chassis Mount   Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Voltage - Input	85 ~ 265 VAC		
Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 12.5A   Power (Watts) 600W   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 88%   Operating Temperature -10°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable, Universal Input   Mounting Type Chassis Mount   Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Voltage - Output 1	48V		
Voltage - Output 4 -   Current - Output (Max) 12.5A   Power (Watts) 600W   Applications ITE (Commercial)   Voltage - Isolation 3kV (3000V)   Efficiency 88%   Operating Temperature -10°C ~ 70°C (With Derating)   Features Adjustable Output, DC Input Capable, Universal Input   Mounting Type Chassis Mount   Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Voltage - Output 2	-		
Current - Output (Max)12.5APower (Watts)600WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Voltage - Output 3	-		
Power (Watts)600WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Voltage - Output 4	-		
ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Current - Output (Max)	12.5A		
Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Power (Watts)	600W		
Efficiency88%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Applications	ITE (Commercial)		
Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Voltage - Isolation	3kV (3000V)		
FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Efficiency	88%		
Mounting TypeChassis MountSize / Dimension7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Operating Temperature	$-10^{\circ}$ C ~ $70^{\circ}$ C (With Derating)		
Size / Dimension 7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)	Features	Adjustable Output, DC Input Capable, Universal Input		
	Mounting Type	Chassis Mount		
Report errors	Size / Dimension	7.48" L x 4.72" W x 2.40" H (190.0mm x 120.0mm x 61.0mm)		
			Report errors?	

### **RWS600B48/CO2** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **RWS600B48/CO2 Payment Methods**





If you have any question about RWS600B48/CO2, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com