

S332T Information



For Reference Only

Part Number S332T

Manufacturer NKK Switches
Category Switches

Switches
Toggle Switches

Description SWITCH TOGGLE DPDT 15A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









S332T Specifications

Manufacturer Part Number \$332T Manufacturer NKK Switches Category Switches Package - Series \$300 Circuit DPDT Switch Function On-On Current Rating 15A (AC), 20A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -		
Category Switches Package - Series S300 Circuit DPDT Switch Function On-On Current Rating 15A (AC), 20A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -	Manufacturer Part Number	S332T
Toggle Switches	Manufacturer	NKK Switches
Package - Series \$300 Circuit DPDT Switch Function On-On Current Rating 15A (AC), 20A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -	Category	Switches
Series \$300 Circuit DPDT Switch Function On-On Current Rating 15A (AC), 20A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -		Toggle Switches
Circuit DPDT Switch Function On-On Current Rating 15A (AC), 20A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -	Package	-
Switch Function On-On Current Rating 15A (AC), 20A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features	Series	S300
Current Rating 15A (AC), 20A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -	Circuit	DPDT
Voltage Rating - AC Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Bushing Thread Ingress Protection Features 125V 30V 30V 30V 30V Standard Round 17.50mm Non-Illumination Non-Illuminated 17.50mm Non-Illuminated 18.50mm Non-Illuminated Non-Illu	Switch Function	On-On
Voltage Rating - DC Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection Features - Standard Round Non-Illumination Non-Illuminated Strew Terminated - Screw Terminal Munt Screw Terminal M12 x 1 Ingress Protection	Current Rating	15A (AC), 20A (DC)
Actuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleScrew TerminalPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-Features-	Voltage Rating - AC	125V
Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features - Features - 17.50mm Circular - Ci	Voltage Rating - DC	30V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Style Screw Terminal Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features	Actuator Type	Standard Round
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -	Actuator Length	17.50mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleScrew TerminalPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-Features-	Illumination Type, Color	-
Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Bushing Thread M12 x 1 Ingress Protection Features Circular - 12.50mm Dia M12 x 1	Mounting Type	Panel Mount
Bushing Thread M12 x 1 Ingress Protection Features	Termination Style	Screw Terminal
Ingress Protection - Features -	Panel Cutout Dimensions	Circular - 12.50mm Dia
Features -	Bushing Thread	M12 x 1
	Ingress Protection	-
Report errors?	Features	-
Report errors:		Report errors?

S332T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

S332T Payment Methods





















S332T Shipping Methods













If you have any question about S332T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com