

S82J-10005A Information

Heisener.com

Part Number S82J-10005A

Manufacturer Omron Automation and Safety

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 5V 100W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









S82J-10005A Specifications

Manufacturer Part Number S82J-10005A Manufacturer Omron Automation and Safety Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series S82J Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 60°C Features Adjustable Output, Load Sharing, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 3.82" L x 7.40" W x 1.97" H (97.0mm x 188.0mm x 50.0mm)	-	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series S82J Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 60°C Features Adjustable Output, Load Sharing, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 3.82" L x 7.40" W x 1.97" H (97.0mm x 188.0mm x 50.0mm)	Manufacturer Part Number	S82J-10005A
Package - Series S82J Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 60°C Features Adjustable Output, Load Sharing, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 3.82" L x 7.40" W x 1.97" H (97.0mm x 188.0mm x 50.0mm)	Manufacturer	Omron Automation and Safety
Package - Series S82J Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 60°C Features Adjustable Output, Load Sharing, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 3.82" L x 7.40" W x 1.97" H (97.0mm x 188.0mm x 50.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series S82J Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 60°C Features Adjustable Output, Load Sharing, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 3.82" L x 7.40" W x 1.97" H (97.0mm x 188.0mm x 50.0mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 60°C Features Adjustable Output, Load Sharing, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 3.82" L x 7.40" W x 1.97" H (97.0mm x 188.0mm x 50.0mm)	Package	-
Number of Outputs1Voltage - Input100 ~ 240 VACVoltage - Output 15VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)20APower (Watts)100WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency83%Operating Temperature-10°C ~ 60°CFeaturesAdjustable Output, Load Sharing, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension3.82" L x 7.40" W x 1.97" H (97.0mm x 188.0mm x 50.0mm)	Series	S82J
Voltage - Input 100 ~ 240 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 60°C Features Adjustable Output, Load Sharing, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 3.82" L x 7.40" W x 1.97" H (97.0mm x 188.0mm x 50.0mm)	Туре	Open Frame
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Applications Voltage - Isolation Size / Dimension 5V Voltage - Output 4 - Current - Output (Max) 20A 100W 100W 1TE (Commercial) 3kV (3000V) 83% Operating Temperature -10°C ~ 60°C Adjustable Output, Load Sharing, Remote Sense, Universal Input Mounting Type Size / Dimension 5V	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -10°C ~ 60°C Features Adjustable Output, Load Sharing, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension	Voltage - Input	100 ~ 240 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Size / Dimension Size / Dimension - Current - Output (Max) 20A 100W 100	Voltage - Output 1	5V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 60°C Features Adjustable Output, Load Sharing, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 3.82" L x 7.40" W x 1.97" H (97.0mm x 188.0mm x 50.0mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 60°C Features Adjustable Output, Load Sharing, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 3.82" L x 7.40" W x 1.97" H (97.0mm x 188.0mm x 50.0mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 60°C Features Adjustable Output, Load Sharing, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 3.82" L x 7.40" W x 1.97" H (97.0mm x 188.0mm x 50.0mm)	Voltage - Output 4	-
ApplicationsITE (Commercial)Voltage - Isolation $3kV$ (3000V)Efficiency 83% Operating Temperature $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ FeaturesAdjustable Output, Load Sharing, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension 3.82 " L x 7.40 " W x 1.97 " H (97.0 mm x 188.0 mm x 50.0 mm)	Current - Output (Max)	20A
Voltage - Isolation $3kV (3000V)$ Efficiency 83% Operating Temperature $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Features Adjustable Output, Load Sharing, Remote Sense, Universal Input Mounting Type Chassis Mount 3.82 " L x 7.40" W x 1.97" H (97.0mm x 188.0mm x 50.0mm)	Power (Watts)	100W
Efficiency 83% Operating Temperature $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Features Adjustable Output, Load Sharing, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 3.82" L x 7.40" W x 1.97" H (97.0mm x 188.0mm x 50.0mm)	Applications	ITE (Commercial)
Operating Temperature $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Features Adjustable Output, Load Sharing, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension $3.82^{\circ}\text{L} \times 7.40^{\circ}\text{W} \times 1.97^{\circ}\text{H} (97.0\text{mm} \times 188.0\text{mm} \times 50.0\text{mm})$	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, Load Sharing, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 3.82" L x 7.40" W x 1.97" H (97.0mm x 188.0mm x 50.0mm)	Efficiency	83%
Mounting Type Chassis Mount Size / Dimension 3.82" L x 7.40" W x 1.97" H (97.0mm x 188.0mm x 50.0mm)	Operating Temperature	-10°C ~ 60°C
Size / Dimension 3.82" L x 7.40" W x 1.97" H (97.0mm x 188.0mm x 50.0mm)	Features	Adjustable Output, Load Sharing, Remote Sense, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	3.82" L x 7.40" W x 1.97" H (97.0mm x 188.0mm x 50.0mm)
		Report errors?

S82J-10005A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

S82J-10005A Payment Methods



















S82J-10005A Shipping Methods













If you have any question about S82J-10005A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com