



SA051C392KAA Information

r.com

Part Number SA051C392KAA Manufacturer AVX Corporation Category

Capacitors Ceramic Capacitors

Description CAP CER 3900PF 100V X7R AXIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SA051C392KAA Specifications

Manufacturer Part Number \$A051C392KAA Manufacturer AVX Corporation Category Capacitors Package Axial Series SpinGuard? SA Capacitance 3900pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.091" Dia x 0.118" L (2.30mm x 3.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Spacing - Lead Style -		
Category Capacitors Package Axial Series SpinGuard? SA Capacitance 3900pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.091" Dia x 0.118" L (2.30mm x 3.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer Part Number	SA051C392KAA
Package Axial Series SpinGuard? SA Capacitance 3900pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.091" Dia x 0.118" L (2.30mm x 3.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer	AVX Corporation
Package Axial Series SpinGuard? SA Capacitance 3900pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.091" Dia x 0.118" L (2.30mm x 3.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Category	Capacitors
Series SpinGuard? SA Capacitance 3900pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.091" Dia x 0.118" L (2.30mm x 3.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 3900pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.091" Dia x 0.118" L (2.30mm x 3.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Package	Axial
Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Ratings Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Axial Size / Dimension 0.091" Dia x 0.118" L (2.30mm x 3.00mm) Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style	Series	SpinGuard? SA
Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.091" Dia x 0.118" L (2.30mm x 3.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Capacitance	3900pF
Temperature Coefficient Ayr Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension O.091" Dia x 0.118" L (2.30mm x 3.00mm) Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - X7R Ayr General Purpose - Hound Hole - Case Axial Case Axial - Lead Spacing - Lead Style	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.091" Dia x 0.118" L (2.30mm x 3.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Voltage - Rated	100V
Features Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.091" Dia x 0.118" L (2.30mm x 3.00mm) Height - Seated (Max) - Thickness (Max) Lead Spacing Lead Style -	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.091" Dia x 0.118" L (2.30mm x 3.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - General Purpose	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.091" Dia x 0.118" L (2.30mm x 3.00mm) Height - Seated (Max) - Thickness (Max) Lead Spacing Lead Style -	Features	-
Failure Rate Mounting Type Through Hole Package / Case Axial Size / Dimension 0.091" Dia x 0.118" L (2.30mm x 3.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Ratings	-
Mounting Type Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Through Hole Axial 0.091" Dia x 0.118" L (2.30mm x 3.00mm) - Case (Max) - Case (Max)	Applications	General Purpose
Package / Case Axial Size / Dimension 0.091" Dia x 0.118" L (2.30mm x 3.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.091" Dia x 0.118" L (2.30mm x 3.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style -	Package / Case	Axial
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.091" Dia x 0.118" L (2.30mm x 3.00mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

SA051C392KAA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SA051C392KAA Payment Methods





















SA051C392KAA Shipping Methods













If you have any question about SA051C392KAA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com