



SDI65-48-UC-P6R Information

Heisener.com

Part Number SDI65-48-UC-P6R

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SDI65-48-UC-P6R Specifications

Manufacturer Part Number SDI65-48-UC-P6R Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Package - Series SDI65-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 1.36A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series SDI65-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 1.36A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Manufacturer Part Number	SDI65-48-UC-P6R
Package - Series SDI65-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 1.36A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Manufacturer	CUI Inc.
Package - Series SDI65-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 1.36A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesSDI65-URegion UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output48VCurrent - Output (Max)1.36APower (Watts)65WNo Load Power Consumption210mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $48V$ Current - Output (Max) $1.36A$ Power (Watts) $65W$ No Load Power Consumption 210mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53° L x 2.09° W x 1.50° H (115.0mm x $53.0mm$ x $38.0mm$)	Package	-
Form Desktop (Class I) Input Type Cord Voltage - Input 90 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 1.36A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Series	SDI65-U
Input TypeCordVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 48V Current - Output (Max) 1.36A Power (Watts) 65W No Load Power Consumption 210mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. $x 5.5\text{mm}$ O.D. $x 9.5\text{mm}$ Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H}$ (115.0mm $\times 53.0\text{mm} \times 38.0\text{mm}$)	Region Utilized	North America
Voltage - Input 90 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 1.36A Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 90 ~ 264 VAC 48V Current - Output (Max) 1.36A 65W No Load Power Consumption 210mW (Max) Positive Center 1TE (Commercial) Level VI, CoC Tier 2 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Form	Desktop (Class I)
Voltage - Output 48V Current - Output (Max) 1.36A Power (Watts) 65W No Load Power Consumption Polarization Polarization Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Input Type	Cord
Current - Output (Max) 1.36A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Voltage - Output	48V
No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Current - Output (Max)	1.36A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0 \text{mm} \times 53.0 \text{mm} \times 38.0 \text{mm})$	Power (Watts)	65W
Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0° C ~ 40° C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.53''$ L x $2.09''$ W x $1.50''$ H (115.0mm x 53.0 mm x 38.0 mm)	No Load Power Consumption	210mW (Max)
Efficiency Level VI, CoC Tier 2 Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0\text{mm} \times 53.0\text{mm} \times 38.0\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.53^{\circ}\text{L} \times 2.09^{\circ}\text{W} \times 1.50^{\circ}\text{H} (115.0\text{mm} \times 53.0\text{mm} \times 38.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Efficiency	Level VI, CoC Tier 2
Size / Dimension 4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.53" L x 2.09" W x 1.50" H (115.0mm x 53.0mm x 38.0mm)
		Report errors?

SDI65-48-UC-P6R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SDI65-48-UC-P6R Payment Methods



















SDI65-48-UC-P6R Shipping Methods













If you have any question about SDI65-48-UC-P6R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com