

# SFV25R-4STE1HLF

Quote

#### SFV25R-4STE1HLF Information

| Part Num<br>Manufact<br>Category<br>Description<br>Package | <ul> <li>Amphenol FCI</li> <li>Connectors, Interconnects</li> <li>FFC, FPC (Flat Flexible) Connectors</li> <li>CONN FPC TOP 25POS 0.50MM R/A</li> </ul> |             |
|--|---|-------------|
| For Reference Only   | For the pricing/inventory/lead time, please contact<br>us<br>Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com                        | Request a 0 |

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# SFV25R-4STE1HLF Specifications

| Manufacturer Part Number     | SFV25R-4STE1HLF  |
|------------------------------|--|
| Manufacturer                 | Amphenol FCI   |
| Category                     | Connectors, Interconnects                                |
|                              | FFC, FPC (Flat Flexible) Connectors                      |
| Package                      | -  |
| Series                       | SFV-R  |
| Flat Flex Type               | FPC  |
| Mounting Type                | Surface Mount, Right Angle                               |
| Connector/Contact Type       | Contacts, Top  |
| Number of Positions          | 25   |
| Pitch                        | 0.020" (0.50mm)  |
| Termination                  | Solder   |
| FFC, FCB Thickness           | 0.33mm   |
| Height Above Board           | 0.071" (1.80mm)  |
| Locking Feature              | Slide Lock   |
| Cable End Type               | Notched  |
| Contact Material             | Phosphor Bronze  |
| Contact Finish               | Tin  |
| Housing Material             | Liquid Crystal Polymer (LCP), Glass Filled, Halogen Free |
| Actuator Material            | Polyphenylene Sulfide (PPS), Glass Filled, Halogen Free  |
| Features                     | Solder Retention, Zero Insertion Force (ZIF)             |
| Voltage Rating               | 50V  |
| Operating Temperature        | -55°C ~ 105°C  |
| Material Flammability Rating | UL94 V-0   |
|                              |  |

## SFV25R-4STE1HLF Guarantees



SERVIC

#### **Quality Guarantees**

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

#### Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## SFV25R-4STE1HLF Payment Methods



If you have any question about SFV25R-4STE1HLF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com