



#### SIT1602BCA3-18S Information



For Reference Only

Part Number SIT1602BCA3-18S

**Manufacturer** SiTIME

Category Crystals, Oscillators, Resonators

**Programmable Oscillators** 

**Description** OSC PROG LVCMOS 1.8V STBY SMD

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## SIT1602BCA3-18S Specifications

Manufacturer Part Number         STT1602BCA3-18S           Manufacturer         SiTIME           Category         Crystals, Oscillators, Resonators           Package         4-SMD, No Lead           Series         SiT1602           Type         MEMS (Silicon)           Programmable Type         MEMS (Silicon)           Available Frequency Range         3.57MHz ~ 77.76MHz           Function         Standby (Power Down)           Output         LVCMOS           Voltage - Supply         1.8V           Frequency Stability         -           Frequency Stability (Total)         ±20ppm, ±25ppm, ±50ppm           Operating Temperature         -20°C ~ 70°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         4.1mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.197" L x 0.126" W (5.00mm x 3.20mm)           Height         0.031" (0.79mm)		
Category         Crystals, Oscillators, Resonators           Package         4-SMD, No Lead           Series         SiT1602           Type         MEMS (Silicon)           Programmable Type         Programmed as Request           Available Frequency Range         3.57MHz ~ 77.76MHz           Function         Standby (Power Down)           Output         LVCMOS           Voltage - Supply         1.8V           Frequency Stability         -           Frequency Stability (Total)         ±20ppm, ±25ppm, ±50ppm           Operating Temperature         -20°C ~ 70°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         4.1mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.197" L x 0.126" W (5.00mm x 3.20mm)           Height         0.031" (0.79mm)	Manufacturer Part Number	SIT1602BCA3-18S
Package         4-SMD, No Lead           Series         SiT1602           Type         MEMS (Silicon)           Programmable Type         Programmed as Request           Available Frequency Range         3.57MHz ~ 77.76MHz           Function         Standby (Power Down)           Output         LVCMOS           Voltage - Supply         1.8V           Frequency Stability         -           Frequency Stability (Total)         ±20ppm, ±25ppm, ±50ppm           Operating Temperature         -20°C ~ 70°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         4.1mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.197" L x 0.126" W (5.00mm x 3.20mm)           Height         0.031" (0.79mm)	Manufacturer	SiTIME
Package         4-SMD, No Lead           Series         SiT1602           Type         MEMS (Silicon)           Programmable Type         Programmed as Request           Available Frequency Range         3.57MHz ~ 77.76MHz           Function         Standby (Power Down)           Output         LVCMOS           Voltage - Supply         1.8V           Frequency Stability         -           Frequency Stability (Total)         ±20ppm, ±25ppm, ±50ppm           Operating Temperature         -20°C ~ 70°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         4.1mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.197" L x 0.126" W (5.00mm x 3.20mm)           Height         0.031" (0.79mm)	Category	Crystals, Oscillators, Resonators
SeriesSiT1602TypeMEMS (Silicon)Programmable TypeProgrammed as RequestAvailable Frequency Range3.57MHz ~ 77.76MHzFunctionStandby (Power Down)OutputLVCMOSVoltage - Supply1.8VFrequency Stability-Frequency Stability (Total)±20ppm, ±25ppm, ±50ppmOperating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)4.1mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height0.031" (0.79mm)		Programmable Oscillators
Type MEMS (Silicon)  Programmable Type Programmed as Request  Available Frequency Range 3.57MHz ~ 77.76MHz  Function Standby (Power Down)  Output LVCMOS  Voltage - Supply 1.8V  Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm  Operating Temperature -20°C ~ 70°C  Spread Spectrum Bandwidth - Current - Supply (Max) 4.1mA  Ratings - Mounting Type Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height 0.031" (0.79mm)	Package	4-SMD, No Lead
Programmable Type Available Frequency Range 3.57MHz ~ 77.76MHz Function Standby (Power Down) Output LVCMOS Voltage - Supply 1.8V Frequency Stability Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.031" (0.79mm)	Series	SiT1602
Available Frequency Range  3.57MHz ~ 77.76MHz  Function  Standby (Power Down)  Output  LVCMOS  Voltage - Supply  1.8V  Frequency Stability	Type	MEMS (Silicon)
Function Output LVCMOS Voltage - Supply 1.8V Frequency Stability - Frequency Stability (Total) Operating Temperature Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension Height Surface Mount  0.031" (0.79mm)  LVCMOS  LVCMOS  1.8V	Programmable Type	Programmed as Request
Output LVCMOS  Voltage - Supply 1.8V  Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -20°C ~ 70°C  Spread Spectrum Bandwidth - Current - Supply (Max) 4.1mA  Ratings - Mounting Type Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height 0.031" (0.79mm)	Available Frequency Range	3.57MHz ~ 77.76MHz
Voltage - Supply  1.8V  Frequency Stability  - Frequency Stability (Total)  Operating Temperature  -20°C ~ 70°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  A.1mA  Ratings  - Mounting Type  Surface Mount  Package / Case  4-SMD, No Lead  Size / Dimension  0.197" L x 0.126" W (5.00mm x 3.20mm)  Height	Function	Standby (Power Down)
Frequency Stability (Total)  Frequency Stability (Total)  Departing Temperature  -20°C ~ 70°C  Spread Spectrum Bandwidth  -  Current - Supply (Max)  Ratings  -  Mounting Type  Surface Mount  Package / Case  4-SMD, No Lead  Size / Dimension  0.197" L x 0.126" W (5.00mm x 3.20mm)  Height  -  1.20°C ~ 70°C  -20°C ~ 70°C  -20°	Output	LVCMOS
Frequency Stability (Total) $\pm 20$ ppm, $\pm 25$ ppm, $\pm 50$ ppm  Operating Temperature $-20^{\circ}$ C $\sim 70^{\circ}$ C  Spread Spectrum Bandwidth $-$ Current - Supply (Max) $4.1$ mA  Ratings $-$ Mounting Type Surface Mount  Package / Case $4-$ SMD, No Lead  Size / Dimension $0.197''$ L x $0.126''$ W $(5.00$ mm x $3.20$ mm)  Height $0.031''$ $(0.79$ mm)	Voltage - Supply	1.8V
Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.1mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Frequency Stability	-
Spread Spectrum Bandwidth  Current - Supply (Max)  Ratings  - Mounting Type Surface Mount  Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height 0.031" (0.79mm)	Frequency Stability (Total)	±20ppm, ±25ppm, ±50ppm
Current - Supply (Max)       4.1mA         Ratings       -         Mounting Type       Surface Mount         Package / Case       4-SMD, No Lead         Size / Dimension       0.197" L x 0.126" W (5.00mm x 3.20mm)         Height       0.031" (0.79mm)	Operating Temperature	-20°C ~ 70°C
Ratings -  Mounting Type Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height 0.031" (0.79mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount  Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height 0.031" (0.79mm)	Current - Supply (Max)	4.1mA
Package / Case 4-SMD, No Lead  Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height 0.031" (0.79mm)	Ratings	-
Size / Dimension       0.197" L x 0.126" W (5.00mm x 3.20mm)         Height       0.031" (0.79mm)	Mounting Type	Surface Mount
Height 0.031" (0.79mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.197" L x 0.126" W (5.00mm x 3.20mm)
Report errors?	Height	0.031" (0.79mm)
		Report errors?

#### SIT1602BCA3-18S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **SIT1602BCA3-18S Payment Methods**



















### SIT1602BCA3-18S Shipping Methods













If you have any question about SIT1602BCA3-18S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com