



SIT3821AC-2D-33EM Information



For Reference Only

Part Number SIT3821AC-2D-33EM

Manufacturer SiTIME

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG LVDS 3.3V EN/DS 10PPM

Package 6-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SIT3821AC-2D-33EM Specifications

Manufacturer Part Number SIT3821AC-2D-33EM Manufacturer SiTIME Category Crystals, Oscillators, Resonators Programmable Oscillators Package 6-SMD, No Lead Series SiT3821 Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function Enable/Disable Output LVDS Voltage - Supply 3.3V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)		
Category Crystals, Oscillators, Resonators Package 6-SMD, No Lead Series SiT3821 Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range IMHz ~ 220MHz Function Enable/Disable Output LVDS Voltage - Supply 3.3V Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Manufacturer Part Number	SIT3821AC-2D-33EM
Package 6-SMD, No Lead Series SiT3821 Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function Enable/Disable Output LVDS Voltage - Supply 3.3V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Manufacturer	SiTIME
Package 6-SMD, No Lead Series SiT3821 Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function Enable/Disable Output LVDS Voltage - Supply 3.3V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Category	Crystals, Oscillators, Resonators
Series SiT3821 Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function Enable/Disable Output LVDS Voltage - Supply 3.3V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height		Programmable Oscillators
Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function Enable/Disable Output LVDS Voltage - Supply 3.3V Frequency Stability + 10ppm Frequency Stability (Total) - 20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height MEMS VCXO Programmed as Request 1MHz ~ 220MHz Programmed as Request Sterley Hit Aut Aut Aut Aut Aut Aut Aut Aut Aut Au	Package	6-SMD, No Lead
Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function Enable/Disable Output LVDS Voltage - Supply 3.3V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.00000000000000000000000000000000000	Series	SiT3821
Available Frequency Range IMHz ~ 220MHz Function Enable/Disable Output LVDS Voltage - Supply 3.3V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Stability Frequency Supply Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.039" (1.00mm) Enable/Disable LVDS 1.00MHz Enable/Disable Enable/Disable Enable/Disable Enable/Disable 1.00MHz 6-SMD, No Lead 1.00Mmy 1.	Туре	MEMS VCXO
Function Enable/Disable Output LVDS Voltage - Supply 3.3V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.039" (1.00mm) Height	Programmable Type	Programmed as Request
OutputLVDSVoltage - Supply3.3VFrequency Stability±10ppmFrequency Stability (Total)-Operating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)55mARatings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.276" L x 0.197" W (7.00mm x 5.00mm)Height0.039" (1.00mm)	Available Frequency Range	1MHz ~ 220MHz
Voltage - Supply Frequency Stability Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Statings - Mounting Type Surface Mount Package / Case Size / Dimension Height 3.3V 3.3V \$100ppm - Surface Mount -20°C ~ 70°C STRA - Surface Mount - Surface Mount - 0.276" L x 0.197" W (7.00mm x 5.00mm) 0.039" (1.00mm)	Function	Enable/Disable
Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Stability Frequency Stability (Total) - Supract Spectrum Bandwidth - Current - Supply (Max) Stability Stabi	Output	LVDS
Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) S5mA Ratings - Mounting Type Surface Mount Package / Case Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - 0.039" (1.00mm)	Voltage - Supply	3.3V
Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) S5mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Frequency Stability	±10ppm
Spread Spectrum Bandwidth - Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Frequency Stability (Total)	-
Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Operating Temperature	-20°C ~ 70°C
Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Current - Supply (Max)	55mA
Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Ratings	-
Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Mounting Type	Surface Mount
Height 0.039" (1.00mm)	Package / Case	6-SMD, No Lead
, ,	Size / Dimension	0.276" L x 0.197" W (7.00mm x 5.00mm)
Report errors?	Height	0.039" (1.00mm)
		Report errors?

SIT3821AC-2D-33EM Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SIT3821AC-2D-33EM Payment Methods



















SIT3821AC-2D-33EM Shipping Methods













If you have any question about SIT3821AC-2D-33EM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com