



Heisener.com

SJTG06RT-22-35P(014) Information

Part Number SJTG06RT-22-35P(014)

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 100POS STRAIGHT PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SJTG06RT-22-35P(014) Specifications

Manufacturer Part NumberSJTG06RT-22-35P(014)ManufacturerAmphenol Aerospace OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypePlug, Male PinsNumber of Positions100Shell Size - Insert22-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 550VDCCurrent Rating-Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Plug, Male Pins Number of Positions 100 Shell Size - Insert 22-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Unrent Rating - Cinnectors, Interconnects Circular Connectors III, VG 96912, SJT NII, VG 96912, SJT NIII, VG 96912, SJT NIII, VG 96912, SJT NIII, VG 96912, SJT Alumin VG 96912, SJT NIII, VG 96912, SJT NIII, VG 96912, SJT NIII, VG 96912, SJT NIII, VG 96912, SJT Alumin V	Manufacturer Part Number	SJTG06RT-22-35P(014)
Circular Connectors Package - Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Plug, Male Pins Number of Positions 100 Shell Size - Insert 22-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating -	Manufacturer	Amphenol Aerospace Operations
Package - MIL-DTL-38999 1 & III, VG 96912, SJT Connector Type Plug, Male Pins Number of Positions 100 Shell Size - Insert 22-35 Shell Size, MIL - Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating -	Category	Connectors, Interconnects
Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Plug, Male Pins Number of Positions 100 Shell Size - Insert 22-35 Shell Size, MIL		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions100Shell Size - Insert22-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 550VDCCurrent Rating-	Package	-
Number of Positions100Shell Size - Insert22-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 550VDCCurrent Rating-	Series	MIL-DTL-38999 I & III, VG 96912, SJT
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating -	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating	Number of Positions	100
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating -	Shell Size - Insert	22-35
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating -	Termination	Crimp
Ingress Protection Environment Resistant Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold Shielded	Orientation	N (Normal)
Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating -	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating -	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 400VAC, 550VDC Current Rating -	Contact Finish	Gold
Current Rating -	Features	Shielded
	Voltage - Rated	400VAC, 550VDC
Report errors?	Current Rating	-
		Report errors?

SJTG06RT-22-35P(014) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SJTG06RT-22-35P(014) Payment Methods



















SJTG06RT-22-35P(014) Shipping Methods













If you have any question about SJTG06RT-22-35P(014), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com